

**300 SERIES**

Non-Service Entrance Rated



Transfer Switches and Type 1 Enclosures are UL 1008 Approved (600 Volt Maximum)

► A = Available For This Configuration

► N/A = Not Available

| AMPS  | FRAME | 2-POLE | 3-POLE | 4-POLE |
|-------|-------|--------|--------|--------|
| 30    | D     | A      | A      | A      |
| 70    | D     | A      | A      | A      |
| 104   | D     | A      | A      | A      |
| 150   | D     | A      | A      | A      |
| 200   | D     | A      | A      | A      |
| 230   | D     | A      | A      | A      |
| 260   | E     | A      | A      | A      |
| 400   | E     | A      | A      | A      |
| 600   | E     | A      | A      | A      |
| 800   | H     | A      | A      | A      |
| 1000  | H     | A      | A      | A      |
| 1,200 | H     | A      | A      | A      |
| 1,600 | G     | N/A    | A      | A      |
| 2,000 | G     | N/A    | A      | A      |
| 2,600 | G     | N/A    | A      | A      |
| 3,000 | G     | N/A    | A      | A      |

**OPTIONAL ENCLOSURES**

| Range by Amp | Type 3R | Type 4 | Type 12 | Type 3R Secure |
|--------------|---------|--------|---------|----------------|
| 30-200       | A       | A      | A       | N/A            |
| 230-400      | A       | A      | A       | N/A            |
| 600          | A       | A      | A       | A              |
| 800-1000     | A       | A      | A       | A              |
| 1200         | A       | A      | A       | A              |
| 1600         | N/A     | A      | A       | A              |
| 2000         | N/A     | N/A    | N/A     | A              |
| 2600-3000    | N/A     | N/A    | N/A     | A              |

**OPTIONAL ACCESSORIES**

|                                                                         |
|-------------------------------------------------------------------------|
| 11BG Deluxe Engine Exerciser (Programmable)                             |
| 14AA/14BA ATS Position Indicating Contacts (2 Normal, 2 Emergency)      |
| 40*B2 Normal and Emergency Service Reversed                             |
| 44A Strip Heater w/Thermostat, External 120V Power Source Required      |
| 44G Strip Heater w/Thermostat, Wired to Load Terminals: 208-600 Volts   |
| 72A Serial Connectivity Module (5110)                                   |
| 72E Ethernet Connectivity Module (5150)                                 |
| 62W Transfer to Emergency Alarm Horn & Silence Switch (City of Chicago) |
| Two (2) Year Basic ATS Standby limited Warranty                         |
| Five (5) Year Comprehensive Extended ATS Standby Limited Warranty       |

► Consult factory for certified dimensions and weights.