


415 kW Diesel Generator Set 208 - 480 Volt

60 Hz / Standby
EPA TIER 3

Engine Technical Data:

Manufacturer:	 John Deere
Model:	6135HF485
Type:	4-Cycle
Aspiration:	Turbo Charged, Air to Air CAC
Cylinder Arrangement:	6 Cylinder Inline
Displacement - Cu. In. (lit):	824 (13.5)
Bore - in. (cm) x stroke - in. (cm):	5.2 (13.2) x 6.5 (16.5)
Compression Ratio:	16:1
Rated RPM:	1800
Max HP Stby (kWm):	617 (460)



Voltage (L-L)	480V	208V	240V	240V
Phase	3	3	3	1
PF	0.8	0.8	0.8	1.0
Hz	60	60	60	60
kW Stby (Prime)	415 (375)	415 (375)	415 (375)	415 (375)
AMPS Stby (Prime)	624 (564)	1441 (1302)	1249 (1128)	1729 (1562)
Generator Model	431CSL6220	572RSL4024	572RSL4024	574RSL4037
Temp Rise	130° C / 27° C	130° C / 27° C	130° C / 27° C	130° C / 27° C
Connection	12 LEAD WYE	12 LEAD WYE	12 LEAD DELTA	12 LEAD ZIG-ZAG

Engine Features

- Radiator Cooled
- Starter and Alternator
- Oil Pump and Filter
- Electric Isochronous Governor
- SAE J1939 Engine Communications
- EPA Tier level 3 Certified

Generator Features

- Brushless Single Bearing
- Automatic Voltage Regulator
 - » Over-excitation Protection
 - » Under-Frequency Compensation
- Available Voltages:
 - » 480/277 3PH 12 wire
 - » 208/120 3PH 12 wire
 - » 240/120 3PH 12 wire
 - » 240/120 1PH 12 wire

DGC 2020 Controller Features

- Microprocessor based, digital control system
- Unit-mounted
- Engine vitals monitored by LCD display:
 - » Oil Pressure
 - » Running Time
 - » Engine Temperature
 - » Safety Shutdowns:
 - ▲ HWT, OC, OS, OP
 - » Battery Voltage
 - » Generator AC Voltage
 - » AC Amperage
 - » Frequency
 - » Continuous Displays
 - ▲ Oil pressure
 - ▲ Engine temperature
 - ▲ Battery voltage
 - ▲ Fuel level


Additional Standard Features

- Main Circuit Breaker (Mounted and wired)
- Flexible Fuel Connectors
- Battery: 24 volt with rack
- Battery Charger: 24 volt 5 amp
- Vibration Isolation Mounts
- Jacket water heater: -20°F w/ valves
- Critical Grade Silencer (Mounted)
- Oil Drain valve with extension
- Radiator duct adapter (OPU only)
- Emergency Stop Push Button

Optional Features


- Sub-base fuel tanks (single or double wall) with or without electrical stub-up area
- Weather Protective and/or Sound Attenuated enclosures
- Remote monitoring panels
- PMG Excitation.

JD415-01



UNIT DIMENSIONS (OPU less silencer)

Unit Type	Dimensions
OPU	140 x 66 x 80 in
WPE	140 x 66 x 104 in
SAE	195 x 66 x 106 in



UNIT WEIGHT (OPU less silencer)

Unit Type	Weight (less tank): lbs (kg)
OPU	8050 (3651)
WPE	9125 (4139)
SAE	10050 (4558)

Dimensions and weights based on standard 480V open power unit. All dimensions and weights may vary with other voltages. Consult factory for installation drawings and accurate weights for your particular unit.

SOUND DATA

Unit Type	Standby		Prime	
	NO LOAD	FULL LOAD	NO LOAD	FULL LOAD
OPU w/ Std Critical Silencer	82 dBA	89 dBA	82 dBA	89 dBA
WPE	81 dBA	88 dBA	81 dBA	88 dBA
SAE	73 dBA	75 dBA	73 dBA	75 dBA

INSTALLATION DATA

	Standby	Prime
Exhaust System		
Gas Temp. (Stack): °F (°C)	880 (471)	801 (427)
Gas Volume at Stack Temp: CFM (m³/min)	2,860 (81)	2,578 (73)
Maximum Allowable Exhaust Restriction: in. H2O (kPa)	40 (10)	40 (10)
Cooling System		
Ambient Capacity of Radiator: °F (°C)	122 (50)	122 (50)
Maximum Allowable Static Pressure on Rad. Exhaust: in. H2O (kPa)	0.5 (0.12)	0.5 (0.12)
Water Pump Flow Rate: Gpm (lit/min)	124 (470)	124 (470)
Heat Rejection to Coolant: BTUM (kW)	13,148 (231)	11,953 (210)
Heat Radiated to Ambient: BTUM (kW)	4,052 (70.9)	3,575 (62.6)
Air Requirements		
Aspirating: CFM (m³/min)	1,201 (34.0)	1,130 (32.0)
Air Flow Required for Rad. Cooled Unit: CFM (m³/min)	23,750 (672)	23,750 (672)
Air Flow Required for Heat Exchanger/Rem. Rad. CFM (m³/min)	Consult Factory For Remote Cooled Applications	
Fuel Consumption		
At 100% of Power Rating: gal/hr (lit/hr)	30.5 (115.7)	26.6 (100.9)
At 75% of Power Rating: gal/hr (lit/hr)	22.0 (83.5)	19.7 (74.8)
At 50% of Power Rating: gal/hr (lit/hr)	15.2 (57.6)	13.7 (51.8)
Fluids Capacity		
Total Oil System: gal (lit)	10.6 (40.0)	10.6 (40.0)
Engine Jacket Water Capacity: gal (lit)	4.25 (16.0)	4.25 (16.0)
System Coolant Capacity: gal (lit)	23.0 (87.1)	23.0 (87.1)