

—STANDARD DIESEL ENGINES SPECIFICATIONS—

	MODEL	RATED		DIMENSIONS							
				LENGTH		WIDTH		HEIGHT		WEIGHT	
		HP	RPM	INCHES	CM	INCHES	CM	INCHES	CM	LBS	KILO
DETROIT DIESEL	2-71	68	@ 2000	32	81	27	69	41	104	960	435
	3-53	101	@ 2800	33	84	27	69	35	89	965	438
	3-71	113	@ 2100	36	91	29	74	41	104	1525	692
	3-53T	131	@ 2500	33	84	29	74	40	102	1000	454
	4-53	140	@ 2800	39	99	27	69	37	94	1110	503
	4-53T	175	@ 2500	40	102	32	81	37	94	1300	590
	4-71	160	@ 2100	42	107	29	74	42	107	1780	807
	4-71T	190	@ 2100	44	112	31	79	44	112	1830	830
	6V53	216	@ 2800	39	99	40	102	37	94	1485	673
	6V53T	223	@ 2500	39	99	37	94	41	104	1695	769
	6-71	238	@ 2100	54	137	29	74	39	99	2190	993
	6V71	238	@ 2100	41	104	39	99	48	122	2010	912
	6V92	276	@ 2100	41	104	39	99	47	119	1960	889
	6V71T	277	@ 2100	41	104	40	102	53	135	2080	943
	6-71T	285	@ 2100	56	142	32	81	50	127	2240	1016
	8V71	318	@ 2100	47	119	39	99	51	130	2310	1048
	6V92T	322	@ 2100	41	104	39	99	52	119	2005	909
	8V71T	362	@ 2100	50	127	40	102	53	135	2495	1132
	8V92	368	@ 2100	48	122	39	99	51	130	2345	1063
	8V92T	430	@ 2100	48	122	39	99	52	132	2395	1086
	12V71	475	@ 2100	60	152	46	117	57	145	3120	1415
	12V92	540	@ 2100	69	175	47	119	50	127	3910	1774
	12V71T	553	@ 2100	70	177	46	117	55	140	3550	1610
	16V71	635	@ 2100	79	201	45	114	58	147	4600	2086
	12V92T	665	@ 2100	68	173	47	119	54	137	4250	1928
	16V71T	725	@ 2100	78	198	47	119	58	147	4800	2177
	16V92	736	@ 2100	79	201	44	112	58	147	4600	2086
	12V149	800	@ 1900	92	235	57	145	67	170	8880	4027
	16V92T	860	@ 2100	79	201	47	119	59	150	4800	2177
	16V92TA	880	@ 2100	79	201	47	119	59	150	4840	2195
	12V149T	1000	@ 1900	91	231	63	160	69	175	9095	4125
	12V149TI	1200	@ 1900	91	231	64	163	69	175	9225	4184
	12V149TIB	1350	@ 1900	91	231	64	163	69	175	9225	4184
	16V149	1060	@ 1900	108	274	54	137	68	173	10540	4780
	16V149T	1325	@ 1900	109	277	64	163	72	183	10840	4916
	16V149TI	1600	@ 1900	104	264	64	163	66	168	10865	4927
	16V149TIB	1800	@ 1900	104	264	64	163	66	168	10865	4927
CUMMINS	NTA855	335	@ 2100	61	155	31	79	52	132	2870	1302
	NTA855	360	@ 2100	61	155	31	79	52	132	2870	1302
	NTA855	400	@ 2100	61	155	31	79	52	132	2870	1302
	NTA855	450	@ 2100	61	155	31	79	52	132	2870	1302
	KT19	450	@ 2100	62	157	32	81	53	135	3600	1633
	KTA19	525	@ 2100	62	157	32	81	54	137	3725	1689
	KTA19	600	@ 2100	62	157	32	81	54	137	3725	1689
	KTTA19	650	@ 2100	62	157	39	99	64	163	3800	1723
	KTTA19	675	@ 2100	62	157	39	99	64	163	3800	1723
	KTTA19	700	@ 2100	62	157	39	99	64	163	3800	1723
	VTA28	725	@ 2100	79	201	51	130	66	168	5800	2630
	VTA28	800	@ 2100	79	201	51	130	66	168	5800	2630
	VTA28	900	@ 2100	79	201	51	130	66	168	5800	2630
	KT38	925	@ 2100	86	218	54	137	65	165	7950	3605
	KTA38	1050	@ 2100	86	218	54	137	65	165	8200	3719
	KTA38	1050	@ 1900	86	218	54	137	65	165	8200	3719
	KTA38	1200	@ 2100	86	218	54	137	65	165	8200	3719
	KTTA38	1350	@ 2100	87	221	59	150	66	168	9250	4195
	KTA50	1600	@ 2100	107	272	59	150	69	175	10700	4853
	KTTA50	1800	@ 1900	107	272	59	150	75	191	10895	4941
	KTTA50	2000	@ 2100	107	272	59	150	75	191	11216	5087
CATERPILLAR	3116T	250	@ 2800	56	142	32	81	34	86	1500	680
	3116TA	350	@ 2800	59	150	32	81	34	86	1500	680
	3208NA	210	@ 2800	58	147	38	97	36	91	2080	943
	3208T	320	@ 2800	59	150	37	94	37	94	2080	943
	3208TA	425	@ 2800	59	150	37	94	37	94	2080	943
	3304BNA	100	@ 2200	60	152	35	89	42	107	1835	832
	3304BT	190	@ 2200	62	157	35	89	42	107	1835	832
	3306BT	280	@ 2200	76	193	37	94	42	107	2470	1120
	3306BTA	350	@ 2200	77	196	37	94	42	107	2470	1120
	3306BTA	355	@ 2200	77	196	37	94	42	107	2470	1120
	3406BT	402	@ 2100	85	216	42	107	49	124	3240	1469
	3406BTA	540	@ 2100	85	216	42	107	49	124	3240	1469
	3408BTA	585	@ 2100	85	216	49	124	55	140	3705	1680
	3412T	540	@ 1800	100	254	55	140	54	137	5420	2458
	3412TA	1000	@ 2100	100	254	55	140	73	185	5420	2458
	3508TA	1150	@ 1800	130	330	68	173	77	196	11500	5215
	3512TA	1750	@ 1800	160	406	67	170	85	216	14400	6531
	3516TA	2800	@ 1925	180	457	67	170	87	221	17700	8027
	3606TA	2722	@ 1000	160	406	69	175	114	290	34500	15646
	3608TA	3630	@ 1000	189	480	69	175	114	290	41800	18957
3612	5440	@ 1000	180	457	68	173	112	284	55300	25079	
3616	7270	@ 1000	216	549	68	173	112	284	65900	29887	