

ECONOFORM and ECONOLOCK



Automatic, Tray Formers


ECONOFORM Tray Formers: Forms corner glue (hot melt) trays. **ECONOLOCK** Tray Formers: Forms corner lock or simplex style locking trays.


The ECONOFORM and ECONOLOCK units are:

- PLC controlled.
- Simple in design and operation.Can accommodate trays with or without
- hinge covers.

 Paperboard and corrugated.

 Productive (up to 1800 trays per hour, standard size range and up to 1200 trays per hour extended size range).





Flat Blank is automatically pulled from a supply magazine with vacuum cups and transported to the forming area.




Mandril plunges blank through tooling cavity and the result is a completed corner glue, cornerlock, or simplex tray.

ENGINEERING DETAILS

Machines available to handle carton sizes outside of range listed above quoted on request. Note: All dimensions are approximate. Subject to change.

STANDARD SIZE RANGE ECONOFORM AND ECONOLOCK—CARTON FORMERS



Size Range: (Carton/Case Size)

Min. 4" x 3" x 1" (102 x 76 x 25mm) Max. 9" x 7" x 3" (229 x 178 x 76mm)

Max Blank Size: 15" x 23" (381 x 584mm)

Speed: Up to 1800 cartons per hour

depending on case size and other factors.

Electrical: 220 volts 50/60 Hz, Single Phase.


Air: 80 psi (5.5 bar). Volume consumption

4.4 CFM, 23.6 SCFM (125 liters/min).

Shipping: Normally less than 400 lbs. (180kg)

EXTENDED SIZE RANGE ECONOFORM AND ECONOLOCK—CARTON FORMERS

Max Blank Size:



Size Range: (Carton/Case Size)

Min. 8" x 6" x 1" (203 x 152 x 25mm) Max: 15" x 12" x 5" 381 x 304 x 127mm)

25" x 39" (635 x 990mm)

Speed: Up to 1200 cartons per hour

depending on case size and

other factors.

Electrical: 220 volts 50/60 Hz, Single Phase.

Air: 80 psi (5.5 bar). Volume consumption

5.5 CFM, 29.5 SCFM (156 liters/min).

Shipping: Normally less than 1200 lbs. (540kg)





Telephone: +1 (781) 986-7500 Fax: +1 (781) 986-1553

www.econocorp.com e-mail: info@econocorp.com

