

General Information

Specifications

Pump Model	Pump Casing		Maximum Impeller Diameter in. (mm)	Performance at Best Efficiency Point (BEP)					Design Pressure psig (bar)
	Inlet Size in. (mm)	Outlet Size in. (mm)		3500 rpm		1750 rpm		Efficiency	
				Capacity gpm (cu. m/hr)	Head ft. (m)	Capacity gpm (cu. m/hr)	Head ft. (m)		
W 20/20	2.0 (51)	2.0 (51)	5.3 (135)	105 (24)	95 (29)	53 (12)	24 (7.3)	65%	260 (18)
W 25/75	4.0 (102)	3.0 (76)	5.9 (150)	352 (80)	118 (36)	176 (40)	29 (8.8)	72%	260 (18)
W 30/25	2.5 (64)	2.0 (51)	6.3 (160)	155 (35)	141 (43)	78 (18)	35 (10.7)	67%	260 (18)
W 30/50	3.0 (76)	2.5 (64)	6.3 (160)	280 (64)	130 (40)	140 (32)	33 (10)	70%	260 (18)
W 30/100	4.0 (102)	3.0 (76)	6.9 (175)	650 (148)	141 (43)	325 (74)	35 (10.7)	82%	200 (14)
W 40/20	2.0 (51)	1.5 (38)	7.1 (180)	120 (27)	190 (58)	60 (14)	47 (14.3)	50%	200 (14)
W 50/25	2.5 (64)	1.5 (38)	7.7 (195)	174 (40)	236 (72)	87 (20)	59 (18)	62%	200 (14)
W 50/50	3.0 (76)	2.0 (51)	7.9 (200)	346 (79)	236 (72)	173 (39)	59 (18)	72%	200 (14)
W 80/50	3.0 (76)	2.0 (51)	10 250	315 (72)	400 (121)	200 (46)	96 (30)	66%	200 (14)
W 50/100	4.0 (102)	3.0 (76)	7.9 (200)	528 (120)	236 (72)	264 (60)	59 (18)	76%	200 (14)
W 70/30	2.5 (64)	1.5 (38)	9.4 (240)	190 (43)	350 (107)	95 (22)	88 (27)	48%	200 (14)
W 100/130	4 (102)	3 (76)	10.6 (270)	670 (152)	400 (121)	380 (86)	110 (33)	78%	200 (14)
W 25/200	6 (152)	4 (102)	11.4 (290)	-	-	1140 (259)	102 (31)	77%	200 (14)
W 60/300	6 (152)	4 (102)	10.2 (260)	-	-	860 (195)	80 (24)	75%	200 (14)