

MQ Power DCA-400SSK

From stationary standby power sources to mobile construction applications, MQ Power's WhisperWatt portable generators will meet your most demanding requirements.

WhisperWatt generators have been engineered to provide the highest reliability and maximum motor starting capability.



Performance Data		
Standby Output	352 kW , 440 kVA	
Prime Output	320 kW , 400 kVA	
Generator RPM	1800 RPMs	
Generator Design	Revolving Field Self-Ventilated Dip-Proof Single Bearing	
Voltage Regulation - (No Load to Full Load)	1.5 %	
Power Factor	0.8	
Armature Connection	Star with Neutral	
Excitation	Brushless with AVR	
No. Poles	4 Pole	
Frequency	60 Hz	
Available Voltages - 3 Phase	208, 220, 240, 416,440, 480 Reconnectable Volts	
Available Voltages - Single Phase	120, 127, 139, 240, 254, 277 Adjustable Volts	
Amps - Single Phase 120V	888.9 (4 Wire) Amps	
Amps - Single Phase 240V	444.4 (4 Wire) Amps	
Amps - Three Phase 240V	962 Amps	
Amps - Three Phase 480V	481 Amps	
Insulation	Class F	
Main Breaker Amps	1000	
Sound Level dB(A) - Full Load at 23 feet	69 dB(A)	
Power Source		
Engine Make / Model	Kamatsu SA6D140AE	
Fuel Consumption	20.4 gal/hr full load	15.8 gal/hr ¾ load
	11.0 gal/hr ½ load	6.6 gal/hr ¾ load
Fuel Tank Capacity	129 Gal Internal	350 Gal Trailer
Dimensions	Without Trailer	With Trailer
Overall Length	166 in. , 420 cm	252 In
Overall Width	55 in. , 140 cm	96 In.
Overall Height	83 in. , 210 cm	114 In.
Approx. Net Wt. Dry	11136 lbs. , 5050 kg.	16,000 includes fuel