

Model: GGHH
KW rating: 100 natural gas standby
100 propane standby
Frequency: 60
Fuel type: Natural gas/propane

➤ **Generator set data sheet**



Our energy working for you.™

Exhaust emission data sheet:	EDS-327
Exhaust emission compliance sheet:	
Sound performance data sheet:	MSP-185
Cooling performance data sheet:	
Prototype test summary data sheet:	PTS-147
Standard set-mounted radiator cooling outline:	0500-3485
Optional set-mounted radiator cooling outline:	
Optional heat exchanger cooling outline:	
Optional remote radiator cooling outline:	

Fuel consumption	Natural gas				Propane			
	Standby kW (kVA)				Prime kW (kVA)			
Ratings	100 (125)				100 (125)			
Load	1/4	1/2	3/4	Full	1/4	1/2	3/4	Full
scfh	428.0	745.0	976.0	1260.0				
m³/hr	12.1	21.1	27.6	35.7				

Engine	Natural gas Standby rating	Prime rating	Propane Standby rating	Prime rating
Engine model	WSG-1068			
Configuration	Cast iron, V 10 cylinder			
Aspiration	Turbocharged			
Gross engine power output, kWm (bhp)	131.3 (176.0)		122.3 (164.0)	
BMEP at rated load, kPa (psi)	1158.3 (168.0)		1158.3 (168.0)	
Bore, mm (in)	90.2 (3.55)		90.2 (3.55)	
Stroke, mm (in)	105.9 (4.17)		105.9 (4.17)	
Rated speed, rpm	1800		1800	
Piston speed, m/s (ft/min)	6.4 (1250.0)		6.4 (1250.0)	
Compression ratio	9.0:1		9.0:1	
Lube oil capacity, L (qt)	5.7 (6.0)		5.7 (6.0)	
Overspeed limit, rpm	2400 ± 50		2400 ± 50	
Regenerative power, kW	16.00		16.00	

Fuel flow				
Minimum operating pressure, kPa (in H ₂ O)	1.7 (7.0)		1.7 (7.0)	
Maximum operating pressure, kPa (in H ₂ O)	3.4 (13.6)		3.4 (13.6)	

Air	Natural gas Standby rating	Prime rating	Propane Standby rating	Prime rating
Combustion air, m³/min (scfm)	6.3 (222.0)		5.8 (204.0)	
Maximum air cleaner restriction, kPa (in H ₂ O)	3.7 (15.0)		3.7 (15.0)	
Alternator cooling air, m³/min (scfm)	37.0 (1308.0)		37.0 (1308.0)	

Exhaust

Exhaust flow at rated load, m ³ /min (cfm)	19.4 (687.0)		17.9 (633.0)	
Exhaust temperature, °C (°F)	640.0 (1184.0)		640 (1184)	
Maximum back pressure, kPa (in H ₂ O)	5.0 (20.0)		5.0 (20.0)	

Standard set-mounted radiator cooling

Ambient design, °C (°F)				
Fan load, kW (HP)	7.3 (9.8)		7.3 (9.8)	
Coolant capacity (with radiator), L (US gal)	33.1 (8.8)		33.0 (8.8)	
Coolant system air flow, m ³ /min (scfm)				
Total heat rejection, MJ/min (Btu/min)				
Maximum cooling air flow static restriction, kPa (in H ₂ O)				

Optional set-mounted radiator cooling

Ambient design, °C (°F)				
Fan load, kW _m (HP)				
Coolant capacity (with radiator), L (US gal)				
Cooling system air flow, m ³ /min (scfm)				
Total heat rejection, MJ/min (Btu/min)				
Maximum cooling air flow static restriction, kPa (in H ₂ O)				

Optional remote radiator cooling¹

Set coolant capacity, L (US gal)				
Max flow rate @ max friction head, jacket water circuit, L/min (US gal/min)				
Heat rejected, jacket water circuit, MJ/min (Btu/min)				
Total heat radiated to room, MJ/min (Btu/min)				
Maximum friction head, jacket water circuit, kPa (psi)				
Maximum static head, jacket water circuit, m (ft)				
Maximum jacket water outlet temp, °C (°F)				

Weights²

Unit dry weight kgs (lbs)	1093 (2410)
Unit wet weight kgs (lbs)	1133 (2498)

Notes:

¹ For non-standard remote installations contact your local Cummins Power Generation representative.

² Weights represent a set with standard features. See outline drawing for weights of other configurations.

Our energy working for you.™

www.cumminspower.com

©2008 | Cummins Power Generation Inc. | All rights reserved | Specifications subject to change without notice | Cummins Power Generation and Cummins are registered trademarks of Cummins Inc. "Our energy working for you." is a trademark of Cummins Power Generation.
D-3385 (5/08)



Alternator data

Natural gas three phase table ¹		105 °C	105 °C	105 °C	105 °C	125 °C	125 °C	125 °C	125 °C	150 °C	150 °C	150 °C
Feature code		B418	B415	B268	B304	B417	B414	B267	B303	B416	B413	B419
Alternator data sheet		208	208	210	207	207	207	209	207	206	207	206
Voltage ranges		110/190 thru 120/208 220/380 thru 240/416	120/208 139/240 240/416 thru 277/480	120/208 139/240 240/416 thru 277/480	347/600	110/190 thru 120/208 220/380 thru 240/416	120/208 139/240 240/416 thru 277/480	120/208 139/240 240/416 thru 277/480	347/600	110/190 thru 120/208 220/380 thru 240/416	120/208 139/240 240/416 thru 277/480	347/600
Surge kW		111	111	112	110	109	109	111	110	108	109	109
Motor starting kVA (at 90% sustained voltage)	Shunt	422	422	563	360	360	360	516	360	313	360	313
	PMG	497	497	663	423	423	423	607	423	368	423	368

Full load current amps at standby rating	120/208 347	127/220 328	139/240 301	220/380 190	240/416 173	277/480 150	347/600 120
--	----------------	----------------	----------------	----------------	----------------	----------------	----------------

Propane three phase table ¹		105 °C	105 °C	105 °C	105 °C	125 °C	125 °C	125 °C	125 °C	150 °C	150 °C	150 °C
Feature code		B418	B415	B268	B304	B417	B414	B267	B303	B416	B413	B419
Alternator data sheet		208	208	210	207	207	207	209	207	206	207	206
Voltage ranges		110/190 thru 120/208 220/380 thru 240/416	120/208 139/240 240/416 thru 277/480	120/208 139/240 240/416 thru 277/480	347/600	110/190 thru 120/208 220/380 thru 240/416	120/208 139/240 240/416 thru 277/480	120/208 139/240 240/416 thru 277/480	347/600	110/190 thru 120/208 220/380 thru 240/416	120/208 139/240 240/416 thru 277/480	347/600
Surge kW		104	104	104	103	102	102	104	103	101	102	102
Motor starting kVA (at 90% sustained voltage)	Shunt	422	422	563	360	360	360	516	360	313	360	313
	PMG	497	497	663	423	423	423	607	423	368	423	368

Full load current amps at standby rating	120/208 347	127/220 328	139/240 301	220/380 190	240/416 173	277/480 150	347/600 120
--	----------------	----------------	----------------	----------------	----------------	----------------	----------------

Natural gas single phase table		105 °C	105 °C	105 °C	105 °C	125 °C	125 °C	125 °C	125 °C			
Feature code		B418	B415	B274	B268	B417	B414	B273	B267			
Alternator data sheet number		208	208	209	210	207	207	208	209			
Voltage ranges		120/240 ²	120/240 ²	120/240 ³	120/240 ³	120/240 ²	120/240 ²	120/240 ³	120/240 ³			
Surge kW		108	108	110	109	106	106	109	108			
Motor starting kVA (at 90% sustained voltage)	Shunt	250	250	305	330	215	215	250	305			
	PMG	290	290	360	385	250	250	290	360			

Full load current amps at standby rating	120/240 ² 278	120/240 ³ 417
--	-----------------------------	-----------------------------

Propane Single phase table		105 °C	105 °C	105 °C	105 °C	125 °C	125 °C	125 °C	125 °C			
Feature code		B418	B415	B274	B268	B417	B414	B273	B267			
Alternator data sheet number		208	208	209	210	207	207	208	209			
Voltage ranges		120/240 ²	120/240 ²	120/240 ³	120/240 ³	120/240 ²	120/240 ²	120/240 ³	120/240 ³			
Surge kW		101	101	103	102	100	100	102	101			
Motor starting kVA (at 90% sustained voltage)	Shunt	250	250	305	330	215	215	250	305			
	PMG	290	290	360	385	250	250	290	360			

Full load current amps at standby rating	120/240 ² 278	120/240 ³ 417
--	-----------------------------	-----------------------------

Notes:

- Single phase power can be taken from a three phase generator set at up to 2/3 set rated 3-phase kW at 1.0 power factor. Also see Note 3 below.
- The broad range alternators can supply single phase output up to 2/3 set rated 3-phase kW at 1.0 power factor.
- The extended stack (full single phase output) and 4 lead alternators can supply single phase output up to full set rated 3-phase kW at 1.0 power factor.

Our energy working for you.™

www.cumminspower.com

©2008 | Cummins Power Generation Inc. | All rights reserved | Specifications subject to change without notice | Cummins Power Generation and Cummins are registered trademarks of Cummins Inc. "Our energy working for you." is a trademark of Cummins Power Generation.
D-3385 (5/08)



Derating factors

Natural gas

Standby/prime	Engine power available up to 594 m (1950 ft) at ambient temperatures up to 40 °C (104 °F). Above 594 m (1950 ft) derate at 4% per 305 m (1000 ft), and 2% per 11 °C (1% per 10 °F) above 40 °C (104 °F).
---------------	--

Propane

Standby/prime	Engine power available up to 305 m (1000 ft) at ambient temperatures up to 25 °C (77 °F). Above 305 m (1000 ft) derate at 4% per 305 m (1000 ft), and 2% per 11 °C (1% per 10 °F) above 25 °C (77 °F).
---------------	--

Ratings definitions

Emergency standby power (ESP):	Limited-time running power (LTP):	Prime power (PRP):	Base load (continuous) power (COP):
Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel Stop power in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power to a constant electrical load for limited hours. Limited Time Running Power (LTP) is in accordance with ISO 8528.	Applicable for supplying power to varying electrical load for unlimited hours. Prime Power (PRP) is in accordance with ISO 8528. Ten percent overload capability is available in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power continuously to a constant electrical load for unlimited hours. Continuous Power (COP) is in accordance with ISO 8528, ISO 3046, AS 2789, DIN 6271 and BS 5514.

Formulas for calculating full load currents:

Three phase output

$$\frac{\text{kW} \times 1000}{\text{Voltage} \times 1.73 \times 0.8}$$

Single phase output

$$\frac{\text{kW} \times \text{SinglePhaseFactor} \times 1000}{\text{Voltage}}$$

Cummins Power Generation

1400 73rd Avenue N.E.
Minneapolis, MN 55432 USA
Phone: 763 574 5000
Fax: 763 574 5298

Warning: Back feed to a utility system can cause electrocution and/or property damage. Do not connect to any building's electrical system except through an approved device or after building main switch is open.

Our energy working for you.™

www.cumminspower.com

©2008 | Cummins Power Generation Inc. | All rights reserved | Specifications subject to change without notice | Cummins Power Generation and Cummins are registered trademarks of Cummins Inc. "Our energy working for you." is a trademark of Cummins Power Generation.
D-3385 (5/08)

