

**Model: DSGAE**  
**Frequency: 60**  
**Fuel type: Diesel**  
**KW rating: 200 standby**  
**180 prime**  
**Emissions level: EPA NSPS Stationary Emergency Tier 3**

➤ **Generator set data sheet**



**Our energy working for you.™**

<b>Exhaust emission data sheet:</b>	<b>EDS-1124</b>
<b>Exhaust emission compliance sheet:</b>	<b>EPA-1173</b>
<b>Sound performance data sheet:</b>	<b>MSP-1102</b>
<b>Cooling performance data sheet:</b>	<b>MCP-210</b>
<b>Prototype test summary data sheet:</b>	<b>PTS-285</b>
<b>Standard set-mounted radiator cooling outline:</b>	<b>A035C611</b>
<b>Optional set-mounted radiator cooling outline:</b>	
<b>Optional heat exchanger cooling outline:</b>	
<b>Optional remote radiator cooling outline:</b>	

<b>Fuel consumption</b>	<b>Standby</b>				<b>Prime</b>				<b>Continuous</b>
	<b>kW (kVA)</b>				<b>kW (kVA)</b>				<b>kW (kVA)</b>
<b>Ratings</b>	200 (250)				180 (225)				
<b>Load</b>	<b>1/4</b>	<b>1/2</b>	<b>3/4</b>	<b>Full</b>	<b>1/4</b>	<b>1/2</b>	<b>3/4</b>	<b>Full</b>	<b>Full</b>
<b>US gph</b>	5.20	8.67	11.63	14.79	4.79	8.16	10.81	13.36	
<b>L/hr</b>	19.7	32.8	44.0	56.0	18.1	30.9	40.9	50.6	

<b>Engine</b>	<b>Standby rating</b>	<b>Prime rating</b>	<b>Continuous rating</b>
Engine manufacturer	Cummins		
Engine model	QSB7-G5 NR3		
Configuration	Cast iron, in-line, 6 cylinder		
Aspiration	Turbocharged and air-to-air aftercooled		
Gross engine power output, kWm (bhp)	242 (324)	208 (279)	
BMEP at set rated load, kPa (psi)	2255 (327)	2033 (295)	
Bore, mm (in)	107 (4.21)		
Stroke, mm (in)	124 (4.88)		
Rated speed, rpm	1800		
Piston speed, m/s (ft/min)	7.4 (1464)		
Compression ratio	17.2:1		
Lube oil capacity, L (qt)	17.5 (18.5)		
Overspeed limit, rpm	2100		
Regenerative power, kW	19		

<b>Fuel flow</b>		
Maximum fuel flow, L/hr (US gph)	106 (28)	
Maximum fuel flow with C174, L/hr (US gph)		
Maximum fuel inlet restriction with clean filter, mm Hg (in Hg)	127 (5)	
Maximum return restriction, mm Hg (in Hg)	152 (6)	

<b>Air</b>	<b>Standby rating</b>	<b>Prime rating</b>	<b>Continuous rating</b>
Combustion air, m <sup>3</sup> /min (scfm)	15.8 (557)	15.3 (539)	
Maximum air cleaner restriction with clean filter, kPa (in H <sub>2</sub> O)	3.7 (15)		
Alternator cooling air, m <sup>3</sup> /min (cfm)	41.3 (1460)		

## Exhaust

Exhaust flow at set rated load, m <sup>3</sup> /min (cfm)	40.5 (1428)	37.7 (1332)	
Exhaust temperature, °C (°F)	510 (949)	484 (903)	
Maximum back pressure, kPa (in H <sub>2</sub> O)	10 (40)	10 (40)	

## Standard set-mounted radiator cooling

Ambient design, °C (°F)	50 (122)		
Fan load, kW <sub>m</sub> (HP)	9.7 (13.0)		
Coolant capacity (with radiator), L (US Gal)	23 (6.1)	23 (6.1)	
Cooling system air flow, m <sup>3</sup> /min (scfm)	351 (12400)		
Total heat rejection, MJ/min (Btu/min)	9.90 (9376)	8.95 (8481)	
Maximum cooling air flow static restriction, kPa (in H <sub>2</sub> O)	0.12 (0.5)		

## Optional set-mounted radiator cooling

Ambient design, °C (°F)			
Fan load, kW <sub>m</sub> (HP)			
Coolant capacity (with radiator), L (US Gal.)			
Cooling system air flow, m <sup>3</sup> /min (scfm)			
Total heat rejection, MJ/min (Btu/min)			
Maximum cooling air flow static restriction, kPa (in. H <sub>2</sub> O)			

## Optional heat exchanger cooling

Set coolant capacity, L (US Gal.)			
Heat rejected, jacket water circuit, MJ/min (Btu/min)			
Heat rejected, aftercooler circuit, MJ/min (Btu/min)			
Heat rejected, fuel circuit, MJ/min (Btu/min)			
Total heat radiated to room, MJ/min (Btu/min)			
Maximum raw water pressure, jacket water circuit, kPa (psi)			
Maximum raw water pressure, aftercooler circuit, kPa (psi)			
Maximum raw water pressure, fuel circuit, kPa (psi)			
Maximum raw water flow, jacket water circuit, L/min (US Gal/min)			
Maximum raw water flow, aftercooler circuit, L/min (US Gal/min)			
Maximum raw water flow, fuel circuit, L/min (US Gal/min)			
Minimum raw water flow at 27 °C (80 °F) inlet temp, jacket water circuit, L/min (US Gal/min)			
Minimum raw water flow at 27 °C (80 °F) inlet temp, aftercooler circuit, L/min (US Gal/min)			
Minimum raw water flow at 27 °C (80 °F) inlet temp, fuel circuit, L/min (US Gal/min)			
Raw water delta P at min flow, jacket water circuit, kPa (psi)			
Raw water delta P at min flow, aftercooler circuit, kPa (psi)			
Raw water delta P at min flow, fuel circuit, kPa (psi)			
Maximum jacket water outlet temp, °C (°F)			
Maximum aftercooler inlet temp, °C (°F)			
Maximum aftercooler inlet temp at 25 °C (77 °F) ambient, °C (°F)			

**Our energy working for you.™**

[www.cumminspower.com](http://www.cumminspower.com)

©2011 Cummins Power Generation Inc. All rights reserved. Cummins Power Generation and Cummins are registered trademarks of Cummins Inc. "Our energy working for you." is a trademark of Cummins Power Generation. Specifications are subject to change without notice.  
D-3517 (8/11)



<b>Optional remote radiator cooling<sup>1</sup></b>	<b>Standby rating</b>	<b>Prime rating</b>	<b>Continuous rating</b>
Set coolant capacity, L (US gal)			
Max flow rate at max friction head, jacket water circuit, L/min (US gal/min)			
Max flow rate at max friction head, aftercooler circuit, L/min (US gal/min)			
Heat rejected, jacket water circuit, MJ/min (Btu/min)			
Heat rejected, aftercooler circuit, MJ/min (Btu/min)			
Heat rejected, fuel circuit, MJ/min (Btu/min)			
Total heat radiated to room, MJ/min (Btu/min)			
Maximum friction head, jacket water circuit, kPa (psi)			
Maximum friction head, aftercooler circuit, kPa (psi)			
Maximum static head, jacket water circuit, m (ft)			
Maximum static head, aftercooler circuit, m (ft)			
Maximum jacket water outlet temp, °C (°F)			
Maximum aftercooler inlet temp at 25 °C (77 °F) ambient, °C (°F)			
Maximum aftercooler inlet temp, °C (°F)			
Maximum fuel flow, L/hr (US gph)			
Maximum fuel return line restriction, kPa (in Hg)			

<b>Weights<sup>2</sup></b>	
Unit dry weight kgs (lbs.)	
Unit wet weight kgs (lbs.)	1361 (3000)

**Notes:**

<sup>1</sup> For non-standard remote installations contact your local Cummins Power Generation representative.

<sup>2</sup> Weights represent a set with standard features. See outline drawing for weights of other configurations.

<b>Derating factors</b>	
<b>Standby</b>	Engine power available up to 1707 m (5600 ft) at ambient temperature up to 40° C (104° F) and 732 m (2400 ft) at 50° C (122° F). Consult your Cummins Power Generation distributor for temperature and ambient requirements outside these parameters.
<b>Prime</b>	Engine power available up to 1707 m (5600 ft) at ambient temperature up to 40° C (104° F) and 732 m (2400 ft) at 50° C (122° F). Consult your Cummins Power Generation distributor for temperature and ambient requirements outside these parameters.
<b>Continuous</b>	

## Ratings definitions

<b>Emergency standby power (ESP):</b>	<b>Limited-time running power (LTP):</b>	<b>Prime power (PRP):</b>	<b>Base load (continuous) power (COP):</b>
Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel Stop power in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power to a constant electrical load for limited hours. Limited Time Running Power (LTP) is in accordance with ISO 8528.	Applicable for supplying power to varying electrical load for unlimited hours. Prime Power (PRP) is in accordance with ISO 8528. Ten percent overload capability is available in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power continuously to a constant electrical load for unlimited hours. Continuous Power (COP) is in accordance with ISO 8528, ISO 3046, AS 2789, DIN 6271 and BS 5514.

**Our energy working for you.™**

[www.cumminspower.com](http://www.cumminspower.com)

## Alternator data

Three Phase Table <sup>1</sup>		105° C	105° C	105° C	125° C	125° C	125° C	150° C	150° C	150° C			
Feature Code		B418	B415	B304	B417	B414	B303	B416	B413	B419			
Alternator Data Sheet Number		212	212	212	212	212	212	211	211	211			
Voltage Ranges		110/190 Thru 120/208 220/380 Thru 240/416	120/208 Thru 139/240 240/416 Thru 277/480	347/600	110/190 Thru 120/208 220/380 Thru 240/416	120/208 Thru 139/240 240/416 Thru 277/480	347/600	110/190 Thru 120/208 220/380 Thru 240/416	120/208 Thru 139/240 240/416 Thru 277/480	347/600			
Surge kW		212	212	215	212	212	215	212	205	214			
Motor Starting kVA (at 90% sustained voltage)	Shunt	770	770	770	770	770	770	672	672	672			
	PMG	920	920	920	920	920	920	791	791	791			
Full Load Current - Amps at Standby Rating		<u>120/208</u> 694	<u>127/220</u> 656	<u>139/240</u> 602	<u>220/380</u> 380	<u>240/416</u> 347	<u>254/440</u> 328	<u>277/480</u> 301	<u>347/600</u> 241				

<sup>1</sup> Single phase power can be taken from a three phase generator set at up to 2/3 set rated 3-phase kW at 1.0 power factor.

## Formulas for calculating full load currents:

### Three phase output

$\frac{\text{kW} \times 1000}{\text{Voltage} \times 1.73 \times 0.8}$

### Single phase output

$\frac{\text{kW} \times \text{Single Phase Factor} \times 1000}{\text{Voltage}}$

### Cummins Power Generation

1400 73<sup>rd</sup> Avenue N.E.  
Minneapolis, MN 55432 USA  
Telephone: 763 574 5000  
Fax: 763 574 5298

**Warning:** Back feed to a utility system can cause electrocution and/or property damage. Do not connect to any building's electrical system except through an approved device or after building main switch is open.

**Our energy working for you.™**

[www.cumminspower.com](http://www.cumminspower.com)