

THE ROMAN FILTER

by  ROSENMUND

separation technology

OVERVIEW

The ROMAN Filter is a simple, manually operated nutsche filter with the pedigree you know and expect from the Rosenmund brand name. It is quality process equipment with the same attention to detail, but in the simplest form demanded by your operational needs and budget.

FEATURES

- **Robust design for 24/7 operation** - Whether at full vacuum, high pressure or both, the filter plate is designed to withstand pressure above the filter plate and full vacuum below, thus allowing a greater differential - that is what the ROMAN is all about!
- **Pharmaceutical design** - It is completely suitable for CIP and WIP with no crevices or product hold-up areas. All metal surfaces are of a high polish finish - 10 to 20 Ra internal, 20 to 30 Ra external.
- **Campaign friendly** - The ROMAN is designed for quick turnaround between campaigns, with its key focus on cleaning and filter media change-out.
- **Qualification friendly** - A dual flange design (positioned top and bottom) allows quick and complete access for visual and physical inspection, (i.e. swab inspection).



ROMAN - Rosenmund Manual Nutsche Filter
Afford the quality and performance you expect from a name.




separation technology

THE ROMAN FILTER


by  **ROSENMUND**

ROMAN Size Range

Model Number	Filtration Area		Diameter		Volume	
	(m ²)	(ft ²)	(mm)	(in)	(Liters)	(Gallons)
Model 12-30L	0.07	0.8	305	12	30	7.9
Model 18-70L	0.16	1.8	457	18	70	18.5
Model 24-125L	0.29	3.1	610	24	125	33
Model 32-225L	0.52	5.6	813	32	225	59.4



The ROMAN Filter has a unique cart assembly used for both lowering the filter plate and moving the filter from location to location. In addition, only one cart assembly is needed for all ROMAN Filter sizes, minimizing required storage.



Specifications

Nozzle Schedule

Noz	Description	Size	Rating	Type
A	Sight glass (top head)	4"	ASME	Tri-clamp
B	Pressure gauge (top head)	1"-1/2"	ASME	Tri-clamp
C	Product inlet (top head)	2"	ASME	Tri-clamp
D	Nitrogen pressure (top head)	1"	ASME	Tri-clamp
E	Spray disc (top head)	3" x 1"	ASME	Tri-clamp
F	Vent (top head)	2"	ASME	Tri-clamp
G	Filtrate outlet (filter base)	1"-1/2"	ASME	Tri-clamp
H	Heating inlet (side wall)	1"	150#	RFSO
J	Heating outlet (side wall)	1"	150#	RFSO

Mechanical

	Process / Shell	Jacket
Design Pressure (psig)	50 / FV	100 / FV
Design Temperature (°F)	-20 to 250	-20 to 250
Corrosion Allowance	None	None
Joint Efficiency	0.7	0.7
Internal Finish	15-20 Ra	
External Finish		20-30 Ra

244 SHEFFIELD STREET MOUNTAINSIDE NJ 07092 TEL 908-317-2585 FAX 908-889-4960
 9110 FORSYTH PARK DRIVE CHARLOTTE NC 28273 FAX 704-588-6866
 WWW.DDPSINC.COM EMAIL SALES@DDPSINC.COM

Copyright © De Dietrich Process Systems, Inc. All rights reserved.



The information contained in this brochure is believed to be reliable general guidelines for consideration of the products and services described herein. The information is general in nature and should not be considered applicable to any specific process or application. De Dietrich Process Systems, Inc. expressly disclaims any warranty, expressed or implied of fitness for any specific purpose in connection with the information contained herein.