

Model: DQGAA
Frequency: 60
Fuel type: Diesel
KW rating: 1250 standby
1100 prime
Emissions: EPA NSPS Stationary Emergency Tier 2

➤ **Generator set data sheet**

Our energy working for you.™



Exhaust emission data sheet:	EDS-1058
Exhaust emission compliance sheet:	EPA-1092
Sound performance data sheet:	MSP-1033
Cooling performance data sheet:	MCP-151
Prototype test summary data sheet:	PTS-265
Standard set-mounted radiator cooling outline:	0500-4357
Optional set-mounted radiator cooling outline:	
Optional heat exchanger cooling outline:	
Optional remote radiator cooling outline:	0500-4309

Fuel consumption	Standby				Prime				Continuous
	kW (kVA)				kW (kVA)				kW (kVA)
Ratings	1250 (1563)				1100 (1375)				
Load	1/4	1/2	3/4	Full	1/4	1/2	3/4	Full	Full
US gph	27.9	51.3	72.9	92.7	25.8	45.6	65.3	82.2	
L/hr	105.6	194.2	276	350.9	97.7	172.6	247.2	311.2	

Engine	Standby rating	Prime rating	Continuous rating
Engine manufacturer	Cummins Inc.		
Engine model	QSK50-G4 NR2		
Configuration	Cast iron, V 16 cylinder		
Aspiration	Turbocharged and low temperature aftercooled		
Gross engine power output, kWm (bhp)	1656 (2220)	1470 (1971)	
BMEP at set rated load, kPa (psi)	1827 (265)	1606 (233)	
Bore, mm (in)	159 (6.25)		
Stroke, mm (in)	159 (6.25)		
Rated speed, rpm	1800		
Piston speed, m/s (ft/min)	9.5 (1875)		
Compression ratio	15:1		
Lube oil capacity, L (qt)	235 (248)		
Overspeed limit, rpm	2100 ±50		
Regenerative power, kW	168		

Fuel flow		
Maximum fuel flow, L/hr (US gph)	757 (200)	
Maximum fuel inlet restriction, kPa (in Hg)	30 (9.0)	
Maximum fuel inlet temperature, °C (°F)	70 (160)	

Air	Standby rating	Prime rating	Continuous rating
Combustion air, m ³ /min (scfm)	130 (4570)	124 (4375)	
Maximum air cleaner restriction, kPa (in H ₂ O)	6.2 (25)		
Alternator cooling air, m ³ /min (cfm)	207 (7300)		

Exhaust

Exhaust flow at set rated load, m ³ /min (cfm)	291 (10290)	261 (9225)	
Exhaust temperature, °C (°F)	417 (782)	372 (702)	
Maximum back pressure, kPa (in H ₂ O)	6.78 (27)		

Standard set-mounted radiator cooling

Ambient design, °C (°F)	40 (104)		
Fan load, kW _m (HP)	45 (60)		
Coolant capacity (with radiator), L (US gal)	541 (143)		
Cooling system air flow, m ³ /min (scfm)	1705 (60150)		
Total heat rejection, MJ/min (Btu/min)	59.88 (56796)	52.43 (49727)	
Maximum cooling air flow static restriction, kPa (in H ₂ O)	0.12 (0.5)		
Maximum fuel return line restriction kPa (in Hg)			

Optional set-mounted radiator cooling

Ambient design, °C (°F)			
Fan load, kW _m (HP)			
Coolant capacity (with radiator), L (US gal)			
Cooling system air flow, m ³ /min (scfm)			
Total heat rejection, MJ/min (Btu/min)			
Maximum cooling air flow static restriction, kPa (in H ₂ O)			
Maximum fuel return line restriction, kPa (in Hg)			

Optional heat exchanger cooling

Set coolant capacity, L (US gal)			
Heat rejected, jacket water circuit, MJ/min (Btu/min)			
Heat rejected, aftercooler circuit, MJ/min (Btu/min)			
Heat rejected, fuel circuit, MJ/min (Btu/min)			
Total heat radiated to room, MJ/min (Btu/min)			
Maximum raw water pressure, jacket water circuit, kPa (psi)			
Maximum raw water pressure, aftercooler circuit, kPa (psi)			
Maximum raw water pressure, fuel circuit, kPa (psi)			
Maximum raw water flow, jacket water circuit, L/min (US gal/min)			
Maximum raw water flow, aftercooler circuit, L/min (US gal/min)			
Maximum raw water flow, fuel circuit, L/min (US gal/min)			
Minimum raw water flow at 27 °C (80 °F) inlet temp, jacket water circuit, L/min (US gal/min)			
Minimum raw water flow at 27 °C (80 °F) inlet temp, aftercooler circuit, L/min (US gal/min)			
Minimum raw water flow at 27 °C (80 °F) inlet temp, fuel circuit, L/min (US gal/min)			
Raw water delta P at min flow, jacket water circuit, kPa (psi)			
Raw water delta P at min flow, aftercooler circuit, kPa (psi)			
Raw water delta P at min flow, fuel circuit, kPa (psi)			
Maximum jacket water outlet temp, °C (°F)			
Maximum aftercooler inlet temp, °C (°F)			
Maximum aftercooler inlet temp at 25 °C (77 °F) ambient, °C (°F)			
Maximum fuel return line restriction, kPa (in Hg)			

Our energy working for you.™

www.cumminspower.com

©2010 Cummins Power Generation Inc. All rights reserved. Cummins Power Generation and Cummins are registered trademarks of Cummins Inc. "Our energy working for you." Is a trademark of Cummins Power Generation. Specifications are subject to change without notice.
D-3333h (7/10)



Optional remote radiator cooling¹	Standby rating	Prime rating	Continuous rating
Set coolant capacity, L (US gal)			
Max flow rate at max friction head, jacket water circuit, L/min (US gal/min)	1779 (470)		
Max flow rate at max friction head, aftercooler circuit, L/min (US gal/min)	492 (130)		
Heat rejected, jacket water circuit, MJ/min (Btu/min)	29.89 (28352)	26.57 (25197)	
Heat rejected, aftercooler circuit, MJ/min (Btu/min)	21.98 (20845)	19 (18025)	
Heat rejected, fuel circuit, MJ/min (Btu/min)			
Total heat radiated to room, MJ/min (Btu/min)	8.0 (7600)	6.86 (6505)	
Maximum friction head, jacket water circuit, kPa (psi)	67 (10)		
Maximum friction head, aftercooler circuit, kPa (psi)	48 (7)		
Maximum static head, jacket water circuit, m (ft)	18.3 (60)		
Maximum static head, aftercooler circuit, m (ft)	18.3 (60)		
Maximum jacket water outlet temp, °C (°F)	104 (220)	100 (212)	
Maximum aftercooler inlet temp at 25 °C (77 °F) ambient, °C (°F)	49 (120)		
Maximum aftercooler inlet temp, °C (°F)	71 (160)	66 (150)	
Maximum fuel flow, L/hr (US gph)			
Maximum fuel return line restriction, kPa (in Hg)			

Weights²

Unit dry weight kgs (lbs)	10989 (24220)
Unit wet weight kgs (lbs)	11493 (25330)

Notes:

¹ For non-standard remote installations contact your local Cummins Power Generation representative.

² Weights represent a set with standard features. See outline drawing for weights of other configurations.

Derating factors

Standby	Engine power available up to 1333 m (4374 ft) at ambient temperatures up to 40 °C (104 °F). Above these elevations, derate at 6.6% per 305 m (1000 ft) and 14.0% per 10 °C (18 °F).
Prime	Engine power available up to 1333 m (4374 ft) at ambient temperatures up to 40 °C (104 °F). Above these elevations, derate at 6.6% per 305 m (1000 ft) and 14.0% per 10 °C (18 °F).
Continuous	

Ratings definitions

Emergency standby power (ESP):	Limited-time running power (LTP):	Prime power (PRP):	Base load (continuous) power (COP):
Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel Stop power in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power to a constant electrical load for limited hours. Limited Time Running Power (LTP) is in accordance with ISO 8528.	Applicable for supplying power to varying electrical load for unlimited hours. Prime Power (PRP) is in accordance with ISO 8528. Ten percent overload capability is available in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power continuously to a constant electrical load for unlimited hours. Continuous Power (COP) is in accordance with ISO 8528, ISO 3046, AS 2789, DIN 6271 and BS 5514.

Our energy working for you.™

www.cumminspower.com

©2010 Cummins Power Generation Inc. All rights reserved. Cummins Power Generation and Cummins are registered trademarks of Cummins Inc. "Our energy working for you." Is a trademark of Cummins Power Generation. Specifications are subject to change without notice. D-3333h (7/10)



Alternator data

Voltage	Connection ¹	Temp rise degrees C	Duty ²	Single phase factor ³	Max surge kVA ⁴	Winding No.	Alternator data sheet	Feature Code
380	Wye, 3-phase	150/105	S/P/C		6716		ADS-331	B595-2
380	Wye, 3-phase	125/105/80	S/P/C		5743		ADS-332	B598-2
380	Wye, 3-phase	105/80	P/C		5521		ADS-331	B659-2
380	Wye, 3-phase	80	P		6716		ADS-332	B687-2
380	Wye, 3-phase	80	S		7695		ADS-333	B660-2
440	Wye, 3-phase	80	P		5521		ADS-330	B689-2
440	Wye, 3-phase	125/105	S/P		5743		ADS-330	B663-2
440	Wye, 3-phase	80	S		6716		ADS-331	B688-2
480	Wye, 3-phase	125/105	S/P		5521		ADS-330	B276-2
480	Wye, 3-phase	105/80	S/P		5743		ADS-330	B600-2
480	Wye, 3-phase	80	S		6716		ADS-331	B601-2
600	Wye, 3-phase	125/105	S/P		5521		ADS-330	B602-2
600	Wye, 3-phase	105/80	S/P		5743		ADS-330	B603-2
600	Wye, 3-phase	80	S		6716		ADS-331	B604-2
4160	Wye, 3-phase	105	P		6204		ADS-322	B312-2
4160	Wye, 3-phase	105/80	S/P		6204		ADS-322	B313-2
4160	Wye, 3-phase	80			7005		ADS-323	B314-2

Notes:

¹ Limited single phase capability is available from some three phase rated configurations. To obtain single phase rating, multiply the three phase kW rating by the Single Phase Factor³. All single phase ratings are at unity power factor.

² Standby (S), Prime (P) and Continuous ratings (C).

³ Factor for the *Single Phase Output from Three Phase Alternator* formula listed below.

⁴ Maximum rated starting kVA that results in a minimum of 90% of rated sustained voltage during starting.

Formulas for calculating full load currents:

Three phase output

$$\frac{\text{kW} \times 1000}{\text{Voltage} \times 1.73 \times 0.8}$$

Single phase output

$$\frac{\text{kW} \times \text{SinglePhaseFactor} \times 1000}{\text{Voltage}}$$

Cummins Power Generation

1400 73rd Avenue N.E.
Minneapolis, MN 55432 USA
Phone: 763 574 5000
Fax: 763 574 5298

Warning: Back feed to a utility system can cause electrocution and/or property damage. Do not connect to any building's electrical system except through an approved device or after building main switch is open.

Our energy working for you.™

www.cumminspower.com