



[Home](#)
[Company](#)
[Literature](#)
[CDS-News](#)
[Service](#)
[Quote Form](#)
[Contact Us](#)
[Careers](#)
[Français](#)



Cool & Size

Pull

Cut

Combination Units

Collect

Texturize

Die Tooling

Auxiliary

Control & Automation

New & In Stock



Cleat Puller Specifications

Cleat Pullers (Fixed Cleats)

Model No.	Contact Length (Width x Length)	Max. conveyor opening	Motor	Drive
CCH25-4V	4" W x 25"	6"	2 HP AC	2 HP AC
CCH36-5V	5" W x 36"	6"	3 HP AC	3 HP AC
CCH36-8V	7.75" W x 36"	6"	3 HP AC	3 HP AC
CCH40-5V	5" W x 40"	6"	3 HP AC	3 HP AC
CCH40-8V	7.75" W x 40"	6"	3 HP AC	3 HP AC
CCH40-12V	11.75" W x 40"	6"	5 HP AC	5 HP AC
CCH48-5V	5" W x 48"	6"	3 HP AC	3 HP AC
CCH48-8V	7.75" W x 48"	6"	3 HP AC	3 HP AC
CCH60-8I	7.75" W x 60"	6"	Two (2): 2 HP AC	5 HP AC
CCH60-12I	11.75" W x 60"	6"	Two (2): 2 HP AC	5 HP AC
CCH60-15I	14.75" W x 60"	6"	Two (2): 2 HP AC	5 HP AC
CCH72-10I	10" W x 72"	6"	Two (2): 2 HP AC	5 HP AC
CCH72-12I	12" W x 72"	6"	Two (2): 2 HP AC	5 HP AC
CCH72-15I	15" W x 72"	6"	Two (2): 2 HP AC	5 HP AC
CCH72-18I	18" W x 72"	6"	Two (2): 2 HP AC	5 HP AC
CCH84-8I	7.75" W x 84"	6"	Two (2): 3 HP AC	7.5 HP AC
CCH84-10I	10" W x 84"	6"	Two (2): 3 HP AC	7.5 HP AC
CCH84-12I	11.75" W x 84"	6"	Two (2): 3 HP AC	7.5 HP AC
CCH84-24I	24" W x 84"	6"	Two (2): 3 HP AC	7.5 HP AC
CCH96-10I	10" W x 96"	6"	Two (2): 3 HP AC	7.5 HP AC
CCH96-15I	15" W x 96"	6"	Two (2): 3 HP AC	7.5 HP AC
CCH120-10V	10" W x 120"	6"	Two (2): 5 HP AC	Two – 7.5 HP AC
CCH144-10V	10" W x 144"	6"	Two (2): 5 HP AC	Two – 7.5 HP AC
CCH48-8ID	7.75" W x 48"	6"	5 HP AC	Chain
CCH72-10ID	10" W x 72"	6"	Two (2): 2 HP AC	Direct

- Choice of DC, Inverter, Vector or Servo motors and drives.
- Dual (D) systems specifications indicate one side and include pneumatic clamping, safety enclosure and remote control
- Controls, speed indicator and inline reducer are custom depending on the material of the finished parts and customer specifications.
- CCH with contact length greater than 60" includes pneumatic clamping, safety enclosure and remote control
- Electrics: 230-460-575V AC / 3PH / 60 Hz, 380-400V AC / 3PH / 50 Hz

Cleat Pullers (Quick Change Cleats)

Model No.	Contact Length (Width x Length)	Max. conveyor opening	Motor	Drive
CCH40-7VQ	7¼" W x 40"	6"	3 HP AC	3 HP AC
CCH48-7VQ	7¼" W x 48"	6"	3 HP AC	3 HP AC
CCH48-10VQ	10" W x 48"	6"	5 HP AC	5 HP AC
CCH60-7IQ	7¼" W x 60"	6"	Two (2): 1 HP AC	3 HP AC
CCH60-10IQ	10" W x 60"	6"	Two (2): 2 HP AC	5 HP AC
CCH72-7IQ	7¼" W x 72"	6"	Two (2): 1 HP AC	3 HP AC
CCH72-10IQ	10" W x 72"	6"	Two (2): 2 HP AC	5 HP AC
CCH72-15IQ	15" W x 72"	6"	Two (2): 2 HP AC	5 HP AC
CCH84-10IQ	10" W x 84"	6"	Two (2): 3 HP AC	7.5 HP AC

Plastic extrusion machine and equipment from CDS

CCH84-15IQ	15" W x 84"	6"	Two (2) : 3 HP AC	7.5 HP AC
CCH96-10IQ	10" W x 96"	6"	Two (2) : 3 HP AC	7.5 HP AC
CCH96-15IQ	15" W x 96"	6"	Two (2) : 3 HP AC	7.5 HP AC
CCH120-10IQ	10" W x 120"	6"	Two (2) : 5 HP AC	Two – 7.5 HP AC
CCH144-10IQ	10" W x 144"	6"	Two (2) : 5 HP AC	Two – 7.5 HP AC
CCH60-10IQD	10" W x 60"	6"	Two (2) : 2 HP AC	Two - 2 HP AC
CCH72-10IQD	10" W x 72"	6"	Two (2) : 2 HP AC	Two - 2 HP AC
CCH96-10IQD	10" W x 96"	6"	Two (2) : 3 HP AC	Two - 3 HP AC
CCH120-10VQD	10" W x 120"	6"	Two (2) : 5 HP AC	Two – 7.5 HP AC

- Q: Quick Change Cleats
- Choice of DC, Inverter, Vector or Servo motors and drives.
- Dual (D) systems specifications indicate one side and include pneumatic clamping, safety enclosure and remote control
- Controls, speed indicator and inline reducer are custom depending on the material of the finished parts and customer specifications.
- CCH with contact length greater than 60" includes pneumatic clamping, safety enclosure and remote control
- Electrics: 230-460-575V AC / 3PH / 60 Hz, 380-400V AC / 3PH / 50 Hz

All CDS machines can be customized according to customer application depending on the material of the extrudate.

Contact CDS for more information on available options.

[<--- Click here to go back to previous page](#)

