

# IVB Series

## Vertical Balers

Safety, reliability and value are just three of the reasons you should choose a vertical baler from International Baler Corporation. The IBC vertical balers feature heavy-duty construction and advanced hydraulics usually found on much larger, more expensive balers. To get the most out of your next vertical baler purchase, call IBC today and put one of our rugged balers to work for you.



IVB-606-HD  
Shown with Bale Door Open and  
Lift Gate in Feed Position



IVB-606-HD



INTERNATIONAL BALER CORPORATION

## Features:



IVB-606-RHC

- Heavy-duty welded construction
- Heavy-duty hydraulic system
- Integrated disconnect providing for lock-out/tag-out procedures
- Single door with retainer dogs
- Automatic push-button cycling
- Bale weights up to 2,000 lbs
- Electrical panel UL Listed
- Adjustable time densification system
- Meets or exceeds all current ANSI Z 245.5 safety standards
- Bale sizer with bale full height

### STRUCTURAL SPECIFICATIONS

	IVB-606-HD	IVB-607-HD	IVB-607-LS	IVB-607-LS-RHC	IVB-727-D
OVERALL HEIGHT	145	147	168	168	179
OVERALL WIDTH	81	81	81	81	91
OVERALL LENGTH	43	43	43	65	59

### IVB-SERIES BALER SPECIFICATIONS

		IVB-606-HD	IVB-607-HD	IVB-607-LS	IVB-607-LS-RHC	IVB-727-D
BALE WEIGHTS IN LBS	OCC	800-1100	900-1200	900-1300	900-1300	1500-2000
	NEWS	900-1300	1000-1350	1100-1400	1000-1400	N/A
BALE SIZE (INCHES)		60 X 30 X 48	60 X 30 X 48	60 X 30 X 48	60 X 30 X 48	72 X 44 X 48
MAIN MOTOR SIZE		15 HP	15 HP	20 HP	20 HP	20 HP
SYSTEM PRESSURE		2200 PSI	2200 PSI	2200 PSI	2200 PSI	2200 PSI
MAIN CYLINDER BORE		6	7	7	7	7
TOTAL FORCE (LBS)		62,200	84,600	84,600	84,600	84,600
RAM FACE PRESSURE (PSI)		38	52	52	52	28
OIL RESERVOIR (GALLONS)		20	20	55	55	55
FEED OPENING (INCHES)		60 X 26	60 X 26	60 X 26	60 X 26	72 X 36
CYCLE TIME (NO LOAD)		45	65	55	60	55
APPROX. SHIPPING WEIGHT (LBS)		5,000	5,500	6,000	6,000	9,500

### INTERNATIONAL BALER CORPORATION

5400 Rio Grande Avenue, Jacksonville, Florida 32254  
P.O. Box 6922, Jacksonville, Florida 32236  
(904) 358-3812 \* (800) 231-9286 \* Fax (904) 358-7013



As part of our continuing product improvement and quality assurance programs, specifications are subject to change without notice and without incurring responsibility to units previously sold.

**VISIT US ON THE WEB: [www.intl-baler.com](http://www.intl-baler.com)**  
**Or email us at: [sales@intl-baler.com](mailto:sales@intl-baler.com)**