

**Quote To :**

Matthew Willis, Resonate Properties  
796 State Route 293  
Eddyville, KY 42038  
Cell 410-952-0317  
[matt@resonatefoods.com](mailto:matt@resonatefoods.com)

**DATE :**  
**QUOTE NO:**  
**EXPIRATION DATE :**

JOB	SALES PERSON	PAYMENT TERMS	DUE DATE
Fermenters			

DESCRIPTION	QUANTITY	UNIT PRICE	LINE TOTAL
4 bbl. ASME (30psi), Fermenter, 304ss Interior, <b>4" Insulation only (No Jacket)</b> , PVRV, Conical Bottom, #4 finish Exterior	2		



**Fermenter Main Features:**



- 304ss interior, 304ss exterior, insulated with 100mm Chloride free PU insulation. Top manway.
- ASME certified model. Pressure tested to 30psi/24 hrs.
- 304ss Butterfly Valve, 1.5" Bottom port.
- Entire body a sanitary #4 finish finish.
- Respective PSI Pressure Vacuum Relief Valve, 2" Tri-Clamp Connection
- CIP Tank Spray Ball has spinner spray head assembly and exterior CIP arm.
- Sanitary Pressure Gauge (Reotemp or equivalent) . — \$145.00 ea.
- Site Glass/Fill level monitor
- Adjustable Levelers to provide a level tank regardless of floor slope.
- NO RACKING ARM OR BLOWOFF LINE REQUIRED


DESCRIPTION	QUANTITY	UNIT PRICE	LINE TOTAL
4 bbl. ASME (30psi), Solvent Storage Tank, 316ss Interior, <b>4" Insulation only (No Jacket)</b> , PVRV, <b>Dish Bottom</b> , #4 finish Exterior	1		



**4bbl. Solvent Storage Tank Main Features:**

- 316ss interior, 304ss exterior, insulated with 100mm Chloride free PU insulation. Top manway.
- ASME certified model. Pressure tested to 30psi/24 hrs.
- 316ss Butterfly Valve, 1.5" Bottom port.
- Entire body a sanitary #4 finish finish.
- Respective PSI Pressure Vacuum Relief Valve, 2" Tri-Clamp Connection
- CIP Tank Spray Ball has spinner spray head assembly and exterior CIP arm.
- Sanitary Pressure Gauge (Reotemp or equivalent) . — \$145.00 ea.
- Site Glass/Fill level monitor
- Adjustable Levelers to provide a level tank regardless of floor slope.
- NO RACKING ARM OR BLOWOFF LINE REQUIRED

DESCRIPTION	QUANTITY	UNIT PRICE	LINE TOTAL
2 bbl. ASME (30psi), Solvent Storage Tank, 316ss Interior, <b>Glycol Jacket</b> , PVRV, <b>Dish Bottom</b> , #4 finish Exterior	1		
	<b>2bbl. Solvent Storage Tank Main Features:</b> <ul style="list-style-type: none"> <li>• 316ss interior, 304ss exterior, insulated with 100mm Chloride free PU insulation. Top manway.</li> <li>• ASME certified model. Pressure tested to 30psi/24 hrs.</li> <li>• 316ss Butterfly Valve, 1.5" Bottom port.</li> <li>• Entire body a sanitary #4 finish finish.</li> <li>• Respective PSI Pressure Vacuum Relief Valve, 2" Tri-Clamp Connection</li> <li>• CIP Tank Spray Ball has spinner spray head assembly and exterior CIP arm.</li> <li>• Sanitary Pressure Gauge (Reotemp or equivalent) . — \$145.00 ea.</li> <li>• Site Glass/Fill level monitor</li> <li>• Adjustable Levelers to provide a level tank regardless of floor slope.</li> <li>• NO RACKING ARM OR BLOWOFF LINE REQUIRED</li> </ul>		
DESCRIPTION	QUANTITY	UNIT PRICE	LINE TOTAL
1 bbl. ASME (30psi), Fermenter, 304ss Interior, <b>4" Insulation only (No Jacket)</b> , PVRV, Conical Bottom, #4 finish Exterior, <b>Caster Wheels</b>	2		
	<b>1bbl. Fermenter Main Features:</b> <ul style="list-style-type: none"> <li>• 304ss interior, 304ss exterior, insulated with 100mm Chloride free PU insulation. Top manway.</li> <li>• ASME certified model. Pressure tested to 30psi/24 hrs.</li> <li>• 304ss Butterfly Valve, 1.5" Bottom port.</li> <li>• Entire body a sanitary #4 finish finish.</li> <li>• Respective PSI Pressure Vacuum Relief Valve, 2" Tri-Clamp Connection</li> <li>• CIP Tank Spray Ball has spinner spray head assembly and exterior CIP arm.</li> <li>• Sanitary Pressure Gauge (Reotemp or equivalent) . — \$145.00 ea.</li> <li>• Site Glass/Fill level monitor</li> <li>• Adjustable Levelers to provide a level tank regardless of floor slope.</li> <li>• NO RACKING ARM OR BLOWOFF LINE REQUIRED</li> <li>• <b>Caster wheels on legs</b></li> </ul>		

DESCRIPTION	QUANTITY	UNIT PRICE	LINE TOTAL
1 bbl. ASME (30psi), Fermenter, 304ss Interior, 4" Insulation only (No Jacket), PVRV, Conical Bottom, #4 finish Exterior	1		
	<b>1bbl. Fermenter Main Features:</b> <ul style="list-style-type: none"> <li>• 304ss interior, 304ss exterior, insulated with 100mm Chloride free PU insulation. Top manway.</li> <li>• ASME certified model. Pressure tested to 30psi/24 hrs.</li> <li>• 304ss Butterfly Valve, 1.5" Bottom port.</li> <li>• Entire body a sanitary #4 finish finish.</li> <li>• Respective PSI Pressure Vacuum Relief Valve, 2" Tri-Clamp Connection</li> <li>• CIP Tank Spray Ball has spinner spray head assembly and exterior CIP arm.</li> <li>• Sanitary Pressure Gauge (Reotemp or equivalent) . — \$145.00 ea.</li> <li>• Site Glass/Fill level monitor</li> <li>• Adjustable Levelers to provide a level tank regardless of floor slope.</li> <li>• NO RACKING ARM OR BLOWOFF LINE REQUIRED</li> </ul>		
		SUB TOTAL :	
		FREIGHT :	
		GRAND TOTAL :	