# TC/TCM Two-stage Liquid Ring Vacuum Pumps



The TC/TCM liquid ring vacuum pumps were created for the chemical, petrochemical and power industries.

These pumps with their integral two stage rotors are able to condense vapors that come off the process and to recover or dispose of them.

The result is a highly reliable and efficient vacuum pump.

#### **Performance** TC 11 TC 10 TC 9 TC 8 TC 7 TC 5 TCM 3 TCM 2 TCM 1 250 500 750 1000 1250 1750 2000 2250 CFM 0 1500

M³/Hr 0

500

1000

1500


2000


2500

3000

#### **Benefits** Integral two-stage impeller High reliability, can attain high vacuum without additional components V-belt or flexible coupling Numerous installation options drive Offered in ductile iron or in High durability and corrosion stainless steel resistance Shrouded rotor blades For strength and reliabilty Single or double mechanical Ability to select the proper

sealing option





TC/TCM 1-5


#### **Dimensions**

seal available

nm in blue

Pump	А	В	С	D	Е	Inlet	Outlet
TCM 1	31.1	15.6	15.5	6.5	1.4	2 in. FLG.	2 in. FLG.
	791	397	394	165	35	50mm FLG.	50mm FLG.
TCM 2	36.9	17.1	17.8	7.9	1.5	2 in. FLG.	2 in. FLG.
	937	435	451	200	38	50mm FLG.	50mm FLG.
TCM 3	38.6	17.1	17.8	7.9	1.5	2 in. FLG.	2 in. FLG.
	981	435	451	200	38	50mm FLG.	50mm FLG.
TC 5	40.3	22.5	22	9.5	1.6	4 in. FLG.	3 in. FLG.
	1022	572	559	241	41	100mm FLG.	80mm FLG.
TC 7	51	28	26	13	2.4	6 in. FLG.	4 in. FLG.
	1282	702	654	330	60	150mm FLG.	100mm FLG.
TC 11	81	40	43	19	3.7	8 in. FLG.	6 in. FLG.
	2060	1005	1080	480	95	200mm FLG.	150mm FLG.

All dimensions are approximate



Gardner Denver Engineered Products Division

3500

## TC 8, TC 9, TC 10 Two-stage **Liquid Ring Vacuum Pumps**



#### Introducing New from Gardner Denver Nash The NASH TC 8, 9, & 10 Two-stage Liquid Ring **Vacuum Pumps**

The NASH TC 8, 9, & 10 bring a new level of design features and benefits to two-stage liquid ring vacuum pumps, especially for the Chemical Process Industry.

#### **Features Benefits** Improved efficiency New, patented air/water separation design "O" ring and gasket sealing options Optimum sealing to your specs ATEX compliant Meets today's industry standards Accepts single, double and cartridge Flexibility to meet your process mechanical seals requirements Removable bearing bracket Easier maintenance ISO & ANSI connections available Meets global requirements All standard NASH TC features Your best guarantee for quality and reliability

### **Performance** TC 11 TC 10 TC 9 TC 8 TC 7 TC 5 TCM 3 TCM 2

TCM 1 250 500 750 1000 1250 1500 1750 2000 CFM 0


1500

2000

2500

3000

3500



All dimensions are approximate

1552

73.3

78.4 1942

846

41.6

44.6

737

35.0

37.0

356

17.0

18.0

80

3.34

3.35

150mm FLG

8 in. FLG.

8 in. FLG.

TC 8

TC 9



M³/Hr 0

500

1000

Gardner Denver Engineered Products Division

100mm FLG

6 in. FLG.

6 in. FLG. 150mm FLG