Model CJ-50-2 Reversible Homogenizer

"All Stainless'

45" immersion length shaft with (3) support rods holding 7" dia. rotor housing.

6" diameter, 3 blade axial flow rotor.

12" adjustable baffle plate with control rod and locking handle.

All major wetted parts Type 316 stainless steel except Rulon mixing head bearing (FDA accepted).

Drive shaft directly coupled to 5 HP, 3600 RPM, TEFC stainless steel washdown Reversible motor for 3/60/230-460

With lifting bracket and stainless steel mounting brackets for bolting to tank spanning supports (support omitted).

Dimensioned per dwg. E9213

Price Ea: \$12,422.00

Additional for 5 HP explosion proof motor (10-11 weeks).

Additional for 7.5 HP stainless steel washdown motor. \$1,102.00

Additional for 7.5 HP explosion proof motor (10-12 weeks). \$1,488.00

Additional for pneumatic portable lift stand. \$5,446.00

Additional for abrasion resistant package including 17-4 PH rotor, stellite bearing, shaft sleeve and protective shaft cover nut. \$972.00

Terms: Net 30 days after credit approval. FOB: Carlstadt, New Jersey Quote valid for 30 days Shipment: 6-8 weeks following receipt of order. If expedited shipment is required, please consult factory. Shortened delivery can be often arranged.

PROCESS DESIGN SERVICE

Arde Barinco Mixer Form