



Temperature range of inlet air	°C	Contact	News Products About Us	Blog	Live	30℃ ~ 300℃	140℃ ~ 300℃ Adjustable	50℃ ~ 300℃
Temperature range of outlet air	°C	Us	40℃ ~ 140℃	Streaming	30℃ ~ 140℃	30℃ ~ 140℃	80℃ ~ 90℃	30℃ ~ 150℃
Spray system	/		Two-fluid nozzle	Two-fluid nozzle	Centrifugal nozzle	Centrifugal nozzle	Centrifugal nozzle	
Precision of temp	°C		±1					
Dryer time	S		1.0 ~ 1.5					
Speed of squirt pump	ml/h		50 ~ 2000	3000	3000	5000	10000	
Nozzle size	mm		0.5/0.7/0.75/1.0/1.5/2.0					
Spray direction	/		Downwards co-current					
Heater Power	/		3KW 220V					
Total power	/		10KW 380V					
Heat source	/		Electric					
Air compressor	/		Built-in oil-free air compressor					
Dried powder restoring rate	%		≥95					≥98
Dimension	mm		940*850*1500	1700*1100*1500	1700*1100*1500	1800*930*2200	2500*1600*2800	
Maximum moisture evaporation	Kg/h		2	3	3	5	10	

We are a young, professional and creative team,

We are customer-centric and responsible team.

Our mission: make your research more accurate and efficient.   [Send Inquiry](#)

Our vision: Become the world's most competitive lab solution provider.

Our value: Sharing & win-win, customer success, be thankful, keep growing, innovation and responsible.