

CRVpro 48 & 65

Introducing the next two members of Welch's CRVpro two-stage rotary vane vacuum pump family.

- ✓ ROBUST VACUUM PUMPS BUILT FOR LONG TERM OPERATION IN DEMANDING APPLICATIONS
- ✓ COOL RUNNING AND LARGE OIL CAPACITIES FOR EXTENDED SERVICE INTERVALS

Welch's CRVpro 48 and 65 are robust, two-stage rotary vane pumps designed for extended service intervals while generating high ultimate vacuum pressure and quick pump downs.

The pumps have forced oil lubrication to maintain proper cooling of pump mechanism. With a focus on cool running operation and large oil capacity separates the CRVpro line from comparable competitive pumps.



Gardner Denver Thomas Inc.
1601 Feehanville Drive
Suite 550
Mt. Prospect, IL 60056

Tel: +1 847-676-8800
Fax: +1 847-677-8606
welch.na@gardnerdenver.com

WELCH
by Gardner Denver

COMMON APPLICATIONS FOR CRVPRO 48 & 65

- ✓ Thin film coating
- ✓ Vacuum drying
- ✓ Vessel or chamber evacuation
- ✓ Refrigeration dehydration
- ✓ Degassing of transformer oils, epoxies, etc.
- ✓ Backing pumps for blowers
- ✓ Freeze drying
- ✓ Distillation

CRVPRO 48 & 65 TECHNICAL SPECIFICATIONS¹

SPECS	CRVpro 48	CRVpro 65
Free Air Displacement @60Hz, CFM (lpm)	33.8 (957)	45.9 (1300)
Free Air Displacement @50Hz, m ³ /hr	48 (800)	65 (1083)
Total Ultimate Vacuum Pressure, Torr(mbar)	0.0015 (0.002)	0.0015 (0.002)
GB Open Full, Total Pressure, Torr (mbar)	0.004 (0.005)	0.005 (0.007)
Motor Pump RPM@60Hz	1720	1720
Motor Power, kw	1.5	2.2
Oil Capacity, liters	4.5	4
Intake Flange	NW40	NW40
Exhaust Flange	NW40	NW40
Noise Level, dBA	58	58
Ambient environmental temp	10 to 40 deg C	10 to 40 deg C
Dimensions, LxWxH, cm (in.)	79.6x26.2x36.9 (29x9x15)	79.6x26.2x36.9 (29x9x15)
Weight, kg (lbs)	62.3 (137)	65.0 (143)

ORDERING INFORMATION	CRVpro 48	CRVpro 65
Three phase; (230-240)/(380-420)V 35% 50Hz (240-265)/(415-460)V 35% 60Hz	3487T-01	3657T-01

Note: CRVpro 48 comes with two NW40 hinge clamps, two NW40 centering rings and 5 liters of Welch Premium Vacuum Pump oil (cat. no. 8995P-11)



EXHAUST FILTER

USEAGE	DESCRIPTION	CAT. NO.
CRVpro 48 & 60	Exhaust Filter made of carbon steel treated to resist corrosion, NW40 flanges	1417D-40

CRVpro2 **CRVpro4,6,8** **CRVpro16,24,30** **CRVpro48,65**

Please check out all our brands for your mission-critical flow control technologies:

THOMAS
by Gardner Denver

OEM Pumps
www.gd-thomas.com

WELCH
by Gardner Denver

Vacuum Pumps & Systems
www.welchvacuum.com

TRICONTINENT
by Gardner Denver

Syringe Pumps
www.tricontinent.com

ZINSSER
ANALYTIC
by Gardner Denver

Lab Automation
www.zinsser-analytic.com

ILS

Syringes
www.microsyringes.com