







	220	280	400	740	740DW	800
						
Overview	Simplex shafted rewinder for trimming and rewinding or bisecting; minimum gap or contact rewinding capabilities.	Duplex liftout slitter rewinder; differential, air differential and lock core capabilities.	Shaftless rewinder with trimming capability; minimum gap or contact rewinding capabilities.	Duplex cantilevered center surface slitter rewinder for narrow width slitting with lift-out unloading.	Duplex cantilevered center surface slitter rewinder for narrow width slitting with cantilevered unloading.	Shafted or individual rewind arm versions with minimum gap or contact rewinding capabilities.
Max Web Width	86" (2185 mm)	86" (2185 mm)	86" (2185 mm)	63" (1600 mm)	40" (1016 mm)	86" (2185 mm)
Max Rewind Diameter	50" (1270 mm)	40" OD (1016 mm OD)	50" * OD (1270 mm)	24" (609 mm)	27" (686 mm)	50" OD (1270 mm OD)
Max Speed	2500 fpm (760 mpm)	2500 fpm (760 mpm)	2500 fpm (760 mpm)	1500 fpm (460 mpm)	1500 fpm (460 mpm)	2500 fpm (760 mpm)
Machine Dimensions (with max roll size)	87" x 55" x (A+102)" (2210 mm x 1400 mm x (A+2590) mm)	74" x 69" x (A+75)" (1880 mm x 1753 mm x (A+1905) mm)	80" x 67" x (A+96)" (2032 mm x 1700 mm x (A+2438) mm)	81" x 63" x 87" (2057 mm x 1600 mm x 2210 mm)	69" x 77" x (A + 74)" (1753 mm x 1956 mm x (A + 2590) mm)	103" x 71" x (A+79)" (2616 mm x 1800 mm x (A+2590) mm)

 **PARKINSON TECHNOLOGIES INC**
 DUSENBERY® CONVERTING SYSTEMS
 MARSHALL AND WILLIAMS PLASTICS
 PARKINSON WINDERS
 KEY FILTERS

100 GOLDSTEIN DRIVE
 WOONSOCKET, RI 02895 USA
 401-762-2100
www.parkinsontechnologies.com
sales@parkinsontechnologies.com