

The Clamco 6600 Series Automatic L Sealer provides the ability to wrap a wide variety of goods at speeds of up to 35 packages per minute without operator assistance. Compact, versatile, simple to set up, and easy to service, the 6600 Series employs specially coated sealing knives for smoke free sealing of all shrink films. Conveniently located mechanical and electrical controls provide ease of operation and fast product change over. The 6600 Series is equipped with obstruction sensors in the sealing head and film advance mechanism, is well guarded, and has a prominently located emergency stop button. Ruggedly built and affordably priced, the U.S. made Clamco 6600 Series is your best buy in automatic L sealers today.

### **Specifications:**

#### **Model 6650**

- Seal area 18" W x 23.5" x 8"H (45cm x 59cm x 20cm).
- All of the standard features, plus:
- Patented lower film cradle with film splitter and pin wheel perforators.
- Horizontal and vertical product detection photoeyes.
- Variable speed conveyors (0-100 FPM).
- Variable speed film advance (0-100 FPM).

#### **Model 6625**

- Seal area 18"W x 23.5"L x 4"H (45cm x 59cm x 10cm).
- All of the standard features, plus:
- Upper film cradle with film splitter and pin wheel perforators.
- Vertical product detection photoeyes.
- Fixed speed conveyors (60 FPM).
- Fixed speed film advance (60 FPM)

#### **All 6600 Series Automatic L-Sealers:**

- Overall dimensions 69"L x 43"W x 58"H (175cm x 109cm x 147cm).
- 120V 20 amp.
- 1 CFM @ 80 PSI.
- Approximate shipping weight 1200 lbs. (544 kgs.).
- Approximate shipping dimensions 76" x 50"W x 62"H (193cm x 127cm x 58cm)

