

# > STEALTH

### **CONTINUOUS MOTION CARTONER**




### **FEATURES & BENEFITS:**

- Speeds up to 400 cartons per minute.
- Small footprint requires less floor space
- HMI touch screen user interface provides visual operation and machine feedback
- Servo-based design means fewer moving parts reducing maintenance and providing greater accuracy at high speeds
- Pre-designed infeed solutions provides for flexibility in handling tubes, vials, bottles, pouches, etc as well as literature insertion
- Powered carton magazine feeder is ergonomically correct and loads easily from either side of the machine
- Standard carton pre-break eliminates carton setup failures
- Captured main flight chain provides increased chain life and squarer cartons
- No tool, quick change carton set-up masks and drop-in plows and guides reduces changeover time
- Fall-through containment shelving, internal lighting and guard design for easy access and clear site lines
- Robust design allows for high-speed, 24/7 applications
- Construction fully supports ANSI/PMMI B1.55.1 safety and cGMP guidelines
- Pharmaceutical validation assistance is included

## **SPECIFICATIONS**

# **STEALTH**<sup>TM</sup>


### **CONTINUOUS MOTION CARTONER**



CENTERS	LENGTH	WIDTH	DEPTH	MAXIMUM SPEEDS
3"	.75 - 1.88 in 19 - 48 mm	.50 - 1.50 in 13 - 38 mm	2.25 - 6.50 in 57 - 165 mm	400 CPM
4.50"	.75 - 3.38 in 19 - 86 mm	.50 - 2.75 in 13 - 70 mm	2.25 - 6.50 in 57 - 165 mm	325 CPM
6"	.75 - 4.0 in 19 <i>-</i> 100 mm	.50 - 2.75 in 13 - 70 mm	2.25 - 6.50 in 57 - 165 mm	250 CPM

### **CARTON STYLES:**

- Economy or FOL Glue End
- Straight Tuck
- Reverse Tuck
- Airplane Tuck
- Fifth Panel Cartons



### **BASE MACHINE:**

- Product Handling Utilizing innovative standard or custom designed modules
- Magazine 72" long, powered, horizontal
- Carton Opening Rotary Carton Setup System with vacuum pre-break
- Product Loading Via barrel cam
- Carton Closing All types of tuck and/or hot melt styles as well as special closures
- No Tool Changeover Drop-in style magazine mask, plows and guides, phase-able flights, quick release handles and mounted scales
- HMI Touch Screen Allen-Bradlev PanelView Plus 1000
- Pharmaceutical Validation Assistance
- Motion Control System Allen-Bradley ControlLogix
- Frame Welded, 3" x 3" tubular painted Steel-It
- Power 230 VAC, 3 Phase, 50-60 Hz
- Air 5 SCFM @ 80 PSI typical
- Maintenance Cluster lubrication, overload detection, electronic manual and troubleshooting

#### **OPTIONAL FEATURES:**

- Automatic Product Handling/Collating
- Insert Feeding
- Coding/Printing
- Bar Code Verification

- Vision Verification
- · Open Flap Detection
- PC-Based HMI Touch Screen
- Stainless Steel Enclosure

