



S E N C O R P TM

www.sencorp-inc.com

CERATEK P-SERIES



Model 12-P/2

Standard Features

- Top Heat
- PLC with Touch Screen HMI
- Closed Loop Temp Control
- Short Cycle Alarm
- High/Low Temp Alarm
- High/Low Pressure Alarm
- Resettable Cycle Counter
- External Output Ports
- CE & ISO 11607 Compliant

Options

- Bottom Heat
- Evacuation/Gas Flush
- Various Width Seal Dies
- Electronic Pressure Regulator
- Recipe Storage
- Data Acquisition
- Removable Work Surface
- Removable Backstop
- Adjustable Backstop
- 220 Volt Conversion



Evacuation/Gas Flush Nozzle

400 Kidds Hill Rd, Hyannis, MA 02601 USA ☎ 508.771.9400 ✉ sales@sencorp-inc.com

We build machines that build business.



SENCORP™

www.sencorp-inc.com



Side Ports

12-P/2 Specifications

Dimensions: 21"H x 16.25"L x 18.5" W

Weight: 120 lbs

24-P/2 Specifications

Dimensions: 21"H x 27.25"L x 18.5" W

Weight: 170 lbs

Construction Materials

Frame: Powder Coated Cast Aluminum

Guarding: Stainless Steel

Seal Jaw Rubber: Molded silicone

Exhaust Filter: Coalescing

Standard Specifications

Utility Requirements:

120 vac, 1 ph, 60 Hz, 15 Amps

220 vac, 1 ph, 50/60 Hz, 7 Amps

Pneumatic: 10—100 PSIG



P-Series LCD Touch Screen HMI and E-Stop



Flat surface sealing dies are available in 1/8", 1/4", 3/8", 1/2" or 1" widths. Custom widths can be quoted upon request.



Removable work surface includes an adjustable stainless steel backstop with an adjustable side-to-side alignment tab.



Operator foot switch activates the sealing cycle.

OTHER CERATEK MACHINES



12-ASL/1 Heat Sealer



MD-2420 Tray Sealer



12-AS/2 Heat Sealer



12-IH/2 Impulse Sealer

400 Kidds Hill Rd, Hyannis, MA 02601 USA ☎ 508.771.9400 ☎ sales@sencorp-inc.com

We build machines that build business.