

ELD – the ideal filling system for bags to be packed laying flat.

ROVEMA

Verpackungsmaschinen GmbH Industriestrasse 1 D 35463 Fernwald Tel: ++49-641-409-0 Fax: ++49-641-409-212 info@rovema.de www.rovema.de

ROVEMA

Verpackungsservice GmbH Industriestraße 3 D 35463 Fernwald Tel: ++49-641-94 00 20 Fax: ++49-641-4 69 76 info@rvs-gmbh.de www.rovema-verpackungsservice.de

ROVEMA

Verpackungsmaschinen Sp. Zo.o. ul. Odynca 51 PL - 02-606 Warszawa Tel.: ++48-22 844 7748 Fax: ++48-22 854 0446 postmaster@rovema.atomnet.pl

ROVEMA Iberica S.A.

C/Mas d'en Cisa, 5, Apdo. Correos N0 55 E 08181 Sentmenat (Barcelona) Tel: ++34-93-7 15 46 00 Fax: ++34-93-7 15 46 38 rovema@rovema.es

ROVEMA

Packaging Machines L.P. 650 Hurricane Shoals Road NW, Lawrenceville, GA 30045 U.S.A Tel: ++1-770-5 13 96 04 Fax: ++1-770-5 13 08 14 rovema@rovema.com www.rovema.com

ROVEMA

Packaging Machines Limited The Coach House The Firs, High Street GB-Whitchurch, Aylesbury HP 22 4 SJ Tel: ++44-12 96-64 20 60 Fax: ++44-12 96-64 15 50 sales@rovema.co.uk

ROVEMA Benelux bv Everdenberg 9, 4902 TT

Postbus 4357, 4900 CJ NL Oosterhout Tel: ++31-162-576 464 Fax: ++31-162-576 465 sales@rovema.nl

ROVEMA Italia s.r.l. Viale P.O.Vigliani, 21 I 20148 Milano Tel: ++39-02 48 01 17 85 Fax: ++39-02 48 00 82 59 rit@rovema-italia.it



Flexible and accurate

Different formations are possible, for example: longitudinal, diagonally, single or multi layer, shingled or side by side. Also exact positioning of heavy and large bags will be ensured

Simple and reliable operation with ROVEMA P@ckControl

The ELD is easy safe to operate with the control system ROVEMA P@ckControl. The monitoring mechanisms and dynamic limit value calculation ensure that incorrect or implausible parameters will not be accepted. In addition, the integrated online help system is available for users to assist, if needed, with convenient navigation via touch-screen.

Benefits and advantages of the ELD

- It is possible to adjust the machine to different spacious conditions or special customer requirements due to its compact design and layout flexibility, as the infeed and discharge directions can be freely chosen during the ELD design.
- Manual or automatic drop distance adjustment for gentle packing of delicate products.
- **Minimized shutdown time** due to rapid size exchange via spindles with digital displays or optional fully automatic size exchange.
- The machine is viewable and accessible from all sides and **easy to clean** wet or with foam because of the increased corrosion prevention (optional).
- Easy and safe operation for anybody with the Rovema system process control ROVEMA-P@ckControl. The operator can also use the integrated online-help with the comfortable navigation on the Touch Screen.
- The vertical filling system ELD can operate as a stand alone machine or **integrated** with other ROVEMA machines into a complete integrated line.

