




Model **RCS-150** cartoner with optional full-height doors and HMI boom mounting

FEATURES & BENEFITS:

- 8' x 4' base machine footprint is among the smallest in the industry.
- Modular design handles carton setup and manual load, semi and fully automatic loading applications at up to 60 cpm on the same low cost machinery platform.
- MGS pre-engineered cartoning infeed systems can **accept and orient incoming products at speeds in excess of 300 ppm to fully automate the cartoning process.**
- Positive vacuum feed carton setup assembly insures **positive carton setups every time.**
- Servo-driven indexing motion carton conveyor system is **easy to access and maintain**, uses fewer parts, **reduces maintenance requirements** and provides accuracy and precise machine movement.
- Heavy-duty welded frame and ball bearings on all drive shafts provides **reliability and ruggedness for 24/7 performance requirements.**
- Screw adjustable carton width and depth adjustments, and the addition of digital readouts, scales and pointers, support **quick, repeatable product changeovers.**
- Operator interface is **simple to operate.**
- Guarding package provides **easy access and to enhance vision lines throughout the entire machine.**
- Construction fully **supports ANSI/PMMA B155.1-2011 safeguarding and cGMP guidelines.**



CARTONS	L	W	D	SPEEDS
Minimum	1 in	.625 in	2.25 in	Up to 60 CPM
Maximum	10 in	4 in	14 in	




CARTON STYLES:

- Reverse Tuck
- Straight Tuck
- Economy End Glue
- Full Flap End Glue
- Sleeves
- Combination Flap Closures

BASE MACHINE:

- **Product Handling** Manual load
- **Magazine** 30" inclined
- **Carton Setup** Reciprocating vacuum arm style
- **Carton Conveyor** Flighted chain conveyor
- **Carton Closing** Hot melt adhesive or tuck style
- **Operator Interface** Standard push-button panel
- **Main Drive** Servo motor
- **Guarding** Polycarbonate upper guards and sheet metal lower guards
- **Frame** Welded and painted
- **Power** 230/460 VAC, 3 Phase (with disconnect), 60 Hz
- **Air** 15-25 SCFM @ 80 PSI, depending on application



OPTIONAL FEATURES:

- Automatic Product Handling & Infeed Systems
- 48" Powered Magazine
- Servo-Driven Load Pusher
- Bar Code Verification Systems
- Coding and Labeling Systems
- Full height guards / doors
- Boom Mounted Control Panel
- Touch Screen HMI
- Casters
- Cluster Lubrication
- Spare Parts Kit