

MANUALLY ADJUSTABLE, SEMI-AUTOMATIC

3M-MATIC™ CASE SEALER 100A BOTTOM BELT DRIVE



Designed for lighter-duty case sealing operations, the semi-automatic 100a is user-friendly and compact; yet, at up to 30 cases per minute, it's fast enough for many single-shift operations. It's easily adjustable for different size case runs. Features of the 3M-Matic Bottom Drive Belt Case Sealer 100a include 3M's advanced, low-impact AccuGlide™ II taping heads with curvilinear tracks; dual masts for extra stability and uniform height adjustment; a height adjustment crank; adjustable side guides; and a sturdy bottom belt drive mechanism with easy-to-install laced replacement belts.

SPECIFICATIONS

Box Size:	Min	Max
Length	6" [150 mm]	No limit
Width	6" [150 mm]	21.5" [545 mm]
Height	4.75" [120 mm]	21.5" [545 mm]
Weight (filled)	5 lbs. [3 kg]	65 lbs. [30 kg]

Tape Width: 36mm minimum to 48 mm maximum.

Machine Operating Rate: Up to 30 boxes per minute depending on box length.

3M-MATIC™ CASE SEALER 200A BOTTOM BELT DRIVE



The 200a is a durable, dependable way to meet basic case sealing needs. It seals up to 30 cases per minute and features a gearmotor drive for heavy duty performance, plus quick box height/width adjustment for added versatility. Other features include 3M's patented AccuGlide™ II taping heads; a unique alternate outboard tape roll mount for the lower head; compression rollers that position each box for precise tape sealing; friction brake tape roll drums; easy-to-install laced replacement belts; and dual masts with twin lead screws for extra stability and to allow for uniform height adjustment.

SPECIFICATIONS

Box Size:	Min	Max
Length	6" [150 mm]	No limit
Width	6" [150 mm]	21.5" [545 mm]
Height	4.75" [120 mm]	24.5" [620 mm]
Weight	5 lbs. [3 kg]	85 lbs. [38 kg]

Tape Width: 36 mm minimum to 48 mm maximum.

Machine Operating Rate: Up to 30 boxes per minute depending on box length.