



Products

Cartoning
Topload
Formers
Closers
Vari-Right
Vari-Straight
Vari-Pitch CFS
Vari-Pitch ST
More Products...
Endload
Wraparound

More KW Products

[Vertical-Form-Fill-Seal](#)

[Special Applications](#)

[Sustainability](#)

Vari-Straight

High-Speed Straight-Line Tri-Seal Topload Carton Closing Machine



Category

Cartoning

Load Type

Topload

[Play Flash Video](#)



[Overview](#)

[Performance](#)

[Optional Features](#)

[System Layout](#)

[Utilities](#)

Performance

Speed

Variable, 30-200 cartons per minute*

Actual speed depends upon machine configuration, carton size and style.

*Ask KW about meeting higher speed requirements.

	Minimum	Maximum	
Length	4" (102mm)	15" (381mm)	
Width	3.25" (83mm)	12" (305mm)	
Depth	1.49" (38mm)	5" (127mm)	

Carton Orientation

Cartons are accepted end leading. Cover on right when viewed looking downstream. Discharged with front tuck leading.

Note: Economy closure flaps are limited to a minimum length of 1". An individual carton combining multiple minimum or maximum dimensions may not be compatible with the standard system.

[Home](#) | [Products](#) | [Solutions by Industry](#) | [Service & Support](#)

[About Us](#) | [Contact Us](#) | [News & Events](#)

© 2013 Kliklok-Woodman. All rights reserved.