



CX1020 | Basic CPU module

The basic CX1020 CPU module has a 1 GHz Intel® CPU. The controller does not require a fan or other rotating components. In addition to the CPU and the chipset, the CX1020 module also contains the main memory, which is available in different sizes. The controller boots from the Compact Flash.

The basic configuration of the CX1020 includes a 64 MB Compact Flash card and two Ethernet RJ 45 interfaces. These interfaces are connected to an internal switch and offer a simple option for creating a line topology without the need for additional Ethernet switches. All other CX family components can be connected via the PC/104 interface that is available on both sides. The passive cooling module is included in the scope of supply. The operating system can be Windows CE or Windows Embedded Standard. The TwinCAT 2 automation software transforms a CX1020 system into a powerful PLC and Motion Control system that can be operated with or without visualisation. In contrast to the CX1010, the CX1020 can also be used for interpolating axis movements with TwinCAT 2 NC I.

Further system interfaces or fieldbus connections can be added to the basic CPU module. The CPU module requires a CX1100 type power supply module. All CX1500 fieldbus modules and all CX1100 power supplies from the CX series can be used in combination with the CX1020.

The Embedded PC CX1020 is also available as the ordering option CX1900-0320 with zero second level cache. Instead of the 1 GHz processor with 512 kB second level cache (L2), a less expensive variant of the processor without a second level cache (L2 = 0 kB) is used. Since the CX1900-0320 has the same 855 GME chipset as the CX1020, none of the basic characteristics of the CX1020 are changed, apart from the slightly lower CPU power.

The order identifier of the basic CPU module is derived as follows:

CX1020-0xxx

0 = without TwinCAT

1 = with TwinCAT 2 PLC run-time

2 = with TwinCAT 2 PLC/NC run-time

3 = with TwinCAT 2 PLC/NC I run-time

0 = without operating system

1 = operating system Windows CE

2 = operating system Windows Embedded Standard

0 = CPU with 2 Ethernet ports

1 = CPU with 2 Ethernet ports + 2 x USB + DVI

Since not all combinations make sense, the table "Ordering information" contains a breakdown of the permissible combinations.

Technical data	CX1020
Processor	Intel® Celeron® M ULV, 1 GHz clock frequency
Flash memory	64 MB Compact Flash card (optionally extendable)
Internal main memory	256 MB DDR RAM (expandable to 512 MB, 1 Gbyte)
Interfaces	2 x RJ 45 (Ethernet, internal switch)
Diagnostics LED	1 x power, 2 x LAN link/activity, TC status, 1 x flash access
Expansion slot	1 x Compact Flash type I+II insert with eject mechanism
Clock	internal battery-backed clock for time and date (battery exchangeable)
Operating system	Microsoft Windows CE or Microsoft Windows Embedded Standard
Control software	TwinCAT 2 PLC runtime, NC PTP runtime, NC I runtime
System bus	16 bit ISA (PC/104)
Power supply	via system bus (through CX1100-xxxx power supply modules)
Max. power loss	11 W (including CX1020-N0xx system interfaces)
Dimensions (W x H x D)	96 mm x 112 mm x 98 mm
Weight	approx. 720 g
Operating/storage temperature	0...+50 °C/-25...+85 °C
Relative humidity	95 %, no condensation
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4
Protection class	IP 20

Ordering information	DVI/USB	no operating system	Win CE	Windows Embedded Standard	no TwinCAT	TwinCAT 2 PLC runtime	TwinCAT 2 NC runtime	TwinCAT 2 NC I runtime
CX1020-0000	—	x	—	—	x	—	—	—
CX1020-0010	—	—	x	—	x	—	—	—
CX1020-0011	—	—	x	—	—	x	—	—
CX1020-0012	—	—	x	—	—	x	x	—
CX1020-0013	—	—	x	—	—	x	x	x
CX1020-0100	x	x	—	—	x	—	—	—
CX1020-0110	x	—	x	—	x	—	—	—
CX1020-0111	x	—	x	—	—	x	—	—
CX1020-0112	x	—	x	—	—	x	x	—
CX1020-0113	x	—	x	—	—	x	x	x
CX1020-0020	—	—	—	x*	x	—	—	—
CX1020-0021	—	—	—	x*	—	x	—	—
CX1020-0022	—	—	—	x*	—	x	x	—
CX1020-0023	—	—	—	x*	—	x	x	x
CX1020-0120	x	—	—	x*	x	—	—	—
CX1020-0121	x	—	—	x*	—	x	—	—
CX1020-0122	x	—	—	x*	—	x	x	—
CX1020-0123	x	—	—	x*	—	x	x	x

Options	
CX1900-0320	option for basic CPU module CX1020: Intel® Celeron® M processor 1 GHz, zero second level cache
CX1900-0120	“Active cooling”: factory conversion of the CX1020 CPU module for active cooling in order to enable flexible installation positions (see documentation). Active cooling takes place via a fan cartridge. This option requires the use of a power supply unit type CX1100-001x.

*CX1020 systems with Microsoft Embedded Standard require Compact Flash with a capacity of at least 2 GB (must be ordered separately).