

MOTOR: For KX-60 is a 1 H.P. and a 2 H.P. for KX-10 of required phase, voltage and cycles. Explosion proof and 1 phase motors available as an extra.

SWITCH: Manual starter with Thermal overload protection.

SPEED: Machine is fitted with a manually set vari-speed pulley to give speeds up to 50 tubes per minute.

CLEANING: This can be done in a short time, even by an unskilled worker.

GENERAL: The machine contains a minimum of moving parts. All moving parts are well guarded, but easily accessible for maintenance. The machine is unusually compact and is entirely self-contained, requiring only connection to an electric outlet. Unit is mounted on casters for easy movement.

GUARANTEE AND SERVICE: Each machine is thoroughly tested before shipment. Each machine is fully guaranteed for six months against faulty construction. Spare parts and skilled service are always available.

DEMONSTRATIONS: Willingly arranged at our factory, using customer's own material and containers if desired.

KX-60 & KX-10 SUPER

AUTOMATIC TUBE FILLERS AND CLOSERS

SHOWING SEALING HEAD TYPE "M-3" FOR PLASTIC AND LAMINATE TUBES

After filling, tubes pass between electrically heated, water-cooled jaws. The first set pre-heat the tubes, the second set gives the final melting and the last, water-cooled jaw, presses and completes the seal with crimp finish and coding; with temperature control. Finally, the tubes pass through a guillotine type cutter to even off the edges and give a final finish. The heated jaws are covered with Teflon impregnated fabric to prevent sticking.

