



Packaging Inc.

10101 Nordel Court, Delta, BC, Canada, V4G 1J8 Phone: (604) 930 9300 Fax: (604) 930 9368 www.wexxar.com

MACHINE SPECIFICATIONS

TAPE SEALERS

Model WST-070 and WST-770

- Description . Automatic case sealer with Pressure Sensitive Tape for corrugated cases. Model WST-070 top seal and model WST-770 top and bottom seal.
 - Frame Construction . Aluminum and plated steel
 - Operation Level . Infeed / Outfeed 23.5 in. (596mm) includes leveling pads ± 1".
 - Controls . Electrical control panel U. L. listed
 . NEMA 12 UL/CSA standard enclosure
 . Meets N.F.P.A.-79 recommendations
 . 24 volt DC power supply built in
 . Magnetic starter with overload relays
 - Power Requirement . 230VAC, 3 Phase, 60Hz (other voltages available)
 . Two 1/3 H.P. TEFC 56C face mounted motors
 - Air Requirement . 0.1 Cu. Ft. per cycle at 90 p.s.i. (6 bar)
 - Tape Applications . DEKKA stainless steel tape applicator heads
 . Alternate makes available as optional equipment
 - Speed . Up to 35 c.p.m. depending on size of case
 - Weight . Approximately 1000 Lb. (365 Kg)
 - Change-Over Time . 2 minutes approximately
 - Case Styles . R.S.C., H.S.C. and C.S.S.C.
 (for other case styles consult your WEXXAR representative)
 - Standard Size Range *

	Length	Inch (mm) Width	Height
Max.	33" (838)	22.5" (572)	24" (610)
Min.	12" (305)	10" (254)	10" (254)
- *For sizes outside of standard range contact your WEXXAR representative
- Safety Guarding . Enclosure of the operating areas of the machine with "Keyed" type electrical interlock switches for maximum operator safety.
 - Other . Auto drain F.R.L.
 . Oil reclassification of airline lubricating oil
 . Full width stopgate
 . Completely adjustable from either side of the machine
 . Cycle limit power shut-off in case of jamming

All above specifications subject to change depending on options chosen and/or case characteristics.