IL & CMS Series





- Automatic inline production
- Available in models running up to 55 wraps per minute
- Ideal for

Sleeve

Wrap

Tray wrapping individual wraps of larger stable product unsupported or pad supported product(s)

innovation

• Low friction, self-tracking infeed and transfer conveyors









IL & CMS Series

4,500 SEAL BAR -TRANSFER BELT _-SHRINK TUNNEL 1,000 3'-3" 1.250 4'-1" DISCHARGE CONVEYOR ELECTRICAL ENCLOSURE FILM SUPPLY INFEED CONVEYOR-SEAL BAR 1.825 835 PNEUMATIC ENCLOSURE

Equipment Benefits



Corporate Headquarters

3301 Gateway Centre Blvd. | Pinellas Park, FL 33782 Tel: 727.578.5000 | Fax: 727.578.1300 Web: www.polypack.com | Email: info@polypack.com



 Heavy gauge, stainless steel construction provides strength, rigidity, cleanliness and minimal maintenance

Model Shown: IL-24L

- Self-leveling, Teflon[®] coated, hot knife
- Pre-programmed acceleration and deceleration for smooth, trouble free operation (reduces film waste)
- Positive, self adjusting, solid stainless steel rod tunnel conveyor (free of belts
- Easy load, low side mounted film roll positioning promotes quick and easy ergonomically friendly film threading
- Engineered as a complete unit with a double insulated tunnel that reduces energy consumption
- Polycarbonate enclosures ensure safety and provide for quick access
- PLC touchscreen interface

