Autoprod's RO-A7 Rotary Filling and Closing System

The RO-A7 fills containers from 125 cc to 2,400 cc at a rate of up to 7,200 cups per hour.

Features:

- Denesting Screw type or custom-engineered method.
 Standard no-cup and optional double-cup sensors.
- Filling Multiple, swirled or layered fills. Liquid, pasty, particulate, dry or powder filling via piston, volumetric, time pressure, auger or weigh-scale filling systems.
 Optional advanced CIP/SIP systems.
- Lidding and sealing Pre-cut or roll stock systems. Heat seal stations are adjustable for time, temperature and pressure.
- Över capping Wipe-on via optional vertical stack, spinning roller or unscrambler.
- · Outfeed Continuous motion belt.



- Multi-fill, layered, side-by-side and concentric deposits
- . Milk, natural yoghurt, stirred yoghurt with fruit pieces, yoghurt with fruit on the bottom of the cup
- · Sweet or sour cream
- Skim-milk guark, guark, cottage cheese, cottage cheese with fruit pieces
- · Puddings, rice puddings, puddings with particulates, custards, flan and gelatine
- · Mousses, whipped creams and toppings, aerated products
- Ice cream with and without large particulates, sorbets, Italian ices, gelati and other frozen desserts
- Jams, jellies, preserves and fruit purees
- Fruit juices and other beverages
- · Dairy and non-dairy dips and sauces
- Soft butter, margarine and other edible fats
- · Soups, stews, gravies and single-serving entrees
- Salads
- · Pet food products
- Isotonic beverages
- Pharmaceuticals
- Dry soup and shredded and grated cheese packaging

Range of Materials:

- Containers Paperboard, foil, laminated paper, plastic and aluminium.
- Lids Roll stock: Paper, foil, plastic or laminated paper/foil/plastic film. Pre-die cut: Paper, foil or plastic.
- Over caps- paper, plastic, foil.

