

# **Shanklin® Model S24B/S24BL**

## **The Heavy Duty Semi-Automatic L-Sealer Series**



- Automatic sealing cycle
- Power film unwind
- Easy loading film inverting head
- Left-to-right or right-to-left product flow
- Easy access electrical controls
- Automatic package discharge
- Brush backed pin perforator
- Hot knife seal system


# The Shanklin® S-series wrappers; quality comes standard

## Description


The Shanklin Model S24B/S24BL L-Frame Sealer is high production semi-automatic wrapping machine. Features of the machine include a 3-point sealing arm suspension with air-magnetic latching, fool-proof arm safety, a precisely controlled heat sealing cycle and a timer-controlled discharge conveyor. Electrical relays are mounted on a U.L. listed panel located behind the easy-to-reach control panel which provides accurate heat for consistent seal. For operator convenience, the unit is equipped with telescoping legs.

Higher production speeds are achieved with the Model S24B/S24BL because it includes several unique features normally found only on our fully automatic L-Sealers; namely, the power film unwind and the film inverting head. The power film unwind permits a free feeding of the film, thus increasing operator efficiency. In addition, better seals (fewer rewaps) are obtained because the film in the seal area is always loose.

### S24B Plan View



### S24BL Plan View



## Shanklin Model S24B/S24BL Specifications

	Model S24B/S24BL
<b>Special Features</b>	<ul style="list-style-type: none"><li>• Power Film Unwind</li><li>• Film Inverting Head</li><li>• Brush Backed Pin Perforator</li><li>• One Piece Hot Knife</li></ul>
<b>Sealer Size</b>	15" Wide x 33" Long (20" Wide and 40" Long Available)
<b>Machine Height</b>	Adjustable from 31" to 43"
<b>Floor Space</b>	4 1/2" X 7"
<b>Package Speeds</b>	20 to 30 Packages/Min.
<b>Power</b>	220V, 20 Amps, 1 Phase (U.L. Listed Control Panel)
<b>Compressed Air</b>	0.5 C.F.M. at 50 P.S.I.
<b>Mechanical Adjustments</b>	<ul style="list-style-type: none"><li>• Discharge Conveyor Height</li><li>• Packing Table and Inverting Head Depth</li><li>• Package Guide Position</li><li>• Film Roll Guides</li><li>• Machine Height</li></ul>
<b>Electrical Controls</b>	<ul style="list-style-type: none"><li>• "Seal" and "Open" Switches</li><li>• Dwell Timer</li><li>• Conveyor Timer</li><li>• Power Unwind Reversing Switch</li></ul>
<b>Pneumatic Controls</b>	<ul style="list-style-type: none"><li>• Flow Control Valves on Sealing Arm</li><li>• Air Filter</li><li>• Lubricator</li><li>• Regulator</li><li>• Gauge</li></ul>
<b>Safety Features</b>	<ul style="list-style-type: none"><li>• Automatic Force Sensor and switches on Seal Jaw provide redundant safety benefits in the event resistance were encountered during closing and prior to locking</li></ul>
<b>Accessories</b>	<ul style="list-style-type: none"><li>• Adjustable Depth Inverting Head</li><li>• Adjustable Height Inverting Head</li><li>• Teflon Coated Inverting Head</li><li>• Special Parts for 18" or 20" Width Capability Available</li><li>• Scrap Removal System (Vacuum or Winder)</li><li>• Static Eliminator</li><li>• Film Centerfolder</li><li>• Casters</li></ul>

Distributed by:



Shrink Packaging  
100 Westford Road  
Ayer, MA 01432  
978-772-3200 Fax: 978-772-5660  
www.shanklincorp.com

**Our Products Protect Your Products®**

Corporate Office: Sealed Air Corporation  
200 Riverfront Boulevard, Elmwood Park, NJ 07407 USA [www.sealedair.com](http://www.sealedair.com)  
® Reg. U.S. Pat. & TMOff. © Sealed Air Corporation (US) 2008. All rights reserved. Printed in the U.S.A. The "9 Dot Logo" and "Sealed Air" are registered trademarks of Sealed Air Corporation (US).

rev 5/1/08