



PD-P3V

Stick packing Machine



10 Lane Stick Pack Machine


Features

- * Easy to adjust photo sensor position.
- * You can control the filling and dropping time for contents during operating.
- * Automatic tension device for film by electronic clutch – reducing film loss considerably.
- * Easy safety management through safety cover and alarm device.
- * The time required is short for the change of parts and there are few consumption articles.

Packing Lane	: 5 Lanes ~ 10 Lanes
Packing Type	: 3 side stick type sealing
I-Mark	: Photo-electric print registration
Packing Size	: W10~50 X L50~200mm
Filling Amount	: 0.5g~30g
Capacity	: 150~300 Packs / Min (5 Lanes) 200~600 Packs / Min (10 Lanes)
Contents	: Sugar, Aspartame, Cream, Coffee Tea Powder, Granule, Etc
Packing Material	: Aluminiumfoil, Polycell, OPP, and other heat sealable film
M/C Dimension	: W1,519 X L 1,420 X H 2,870 mm (10 Lane Machine)
Weight	: About 1,500Kg
Power	: 3Ph, 220/380V, 50 or 60 Hz
Pneumatic	: 6kg/ cm^2



6 Lane Stick Pack Machine



(株)韓独自動機
HANDOK AUTO. MACHINE CO., LTD.

본사(공장): 京畿道 金浦市 豊舞洞 662-113
TEL: (031) 982-0775(대)
FAX: (031) 984-2532
662-113, POONGMOO-DONG, KIMPO-SI, KYONGGI-DO, KOREA.

Overseas Consulting :

SPACK SYS.

Tel : +82-31-811-9003
Fax : +82-31-811-9005
E-mail : webmaster@spacksys.com