




CAPSTONE F *Series*

F Series Closer
Closes shelf-ready cases and standard shippers


CAPSTONE F *Series*



FEATURES




Auto-Open




Self-Tensioning Belts




1 Minute Changeover




Compact Footprint



Cabrio Case® SRP



Shelf-Ready Cases



Economical Shippers



Pass-Through Mode



Maximum Finished Case Size



Speeds up to 55/min

CAPSTONE F *Series*



KEY FEATURES

Closes a Wide Range of Case Styles
Closes Corrugated Material and Paperboard
Compact-Inline Footprint
Simple 1 Minute Tool-Less Changeover



UTILITIES

Power 480v 60hz 3ph
Air 15 SCFM @ 80PSIG



DIMENSIONS

Weight 2,400 lbs.
Overall Length 13' (3,965 mm) *Includes tunnel guarding
Overall Width 5' (1,525 mm)
Overall Height 6' 5" (1,985 mm)



MACHINE LAYOUT

Right Hand Inline Discharge
Left Hand Inline Discharge



CONTROL SYSTEM

PLC Allen-Bradley Compact Logix
HMI Allen-Bradley Panelview 700 or 1000
Safety System Category II or III



MACHINE OPTIONS

Backside Doors Easy Access with Doors Surrounding Machine
Open Flap Detection Operator Notification for Open Flaps
Reject Conveyor Removal of Rejected Cases
Elevation Top of Conveyor Height 24" or 36"
Changeover Push-Button Changeover Available
Status Glow Bright Internal LED Status Lights



ENCLOSURE CONFIGURATIONS

Main Panel NEMA 4 (SS) or NEMA 4X(SS)
Panel Cooling Vortex, Heat Exchanger or Air-Conditioner

Please call (800) 328-5558 to discuss custom configurations and applications.



Delkor Systems, Inc. | 4300 Round Lake Rd. West, St. Paul, MN 55112
1.800.328.5558 | www.delkorsystems.com | info@delkorsystems.com