

## O/K PACKAGING SYSTEM

### OK Superformer Case Erector

### Features:

### Benefits:

Quick and easy size change Automatic case squaring system

Increased production efficiency and flexibility Consistency for automatic lines and enhanced cosmetics

Tape and case monitoring package Single frame, in line design Stainless steel exterior finish Operator friendly and reliability
Ease of set up, training and operation
Clean and durable finish, preferred in food and
other industries

Superformer 1

### **Technical specifications:**

#### Case range: Min. I x w x h 8.00" x 6.00" x 3.00" 8.00" x 8.00" x 6.00" Max. I x w x h 18.00" x 14.00" x 16.00" 24.00" x 20.00" x 24.00" Speed: Tape applicator: High quality tape applicator suitable for all standard pressure sensitive tapes up to 2" wide (3"optional) and 13" diameter rolls. Open tape feed path. Case magazine: Horizontal, belt driven, indexing magazine, length 40". Electric: 480V, 3 Phase, 60Hz standard. Other voltages to requirement. Pneumatic: 70 - 100 Psi, 1/2" supply. PLC controls with operator fault finding display. Controls: Signals for low tape, no tape, tape not applied, low case magazine and empty case magazine. Finish: Stainless steel frame and exterior, zinc plated and painted interior.

Superformer 1M

## **OK Superformer Options:**

- Smaller case range
- All stainless steel
- Case magazine 60" long


### O/K Product Range:


- Bag Inserters and Bag Closers
- Top Taping Machines
- Conveyor Systems and Product Fillers

O/K International's equipment can be added to enhance existing lines or can be supplied as a complete automatic system.

# Superformer 1M


Machine Handling:





## Superformer 1

Right to left or left to right to requirement.





O/K International Corporation
73 Bartlett Street
Marlborough, MA 01752
Phone 508.303.8286
Fax 508.303.8207
www.okcorp.com