



At a Glance

- Fast changeovers supported by scales, pointers, quick release handles, and HMI graphical guides
- Heavy-duty welded tubular frame made of mild steel, stainless steel, or low pressure wash down
- Positive case selection/transfer



[_\(/sustainability/#didyouknow\).](https://sustainability/#didyouknow)

Buy your [boxes \(/packaging-materials/corrugated-shipping-cases/\)](/packaging-materials/corrugated-shipping-cases/) from us, and get a discount on this Pearson case erector!

Click to enlarge



[\(/images/square/machinespearsonCE25a.jpg\)](/images/square/machinespearsonCE25a.jpg)



[\(/images/square/machinespearsonCE25b.jpg\)](/images/square/machinespearsonCE25b.jpg)



[\(/www.youtube.com/embed/ EAJQVlGYko\)](https://www.youtube.com/embed/EAJQVlGYko)

Recommended



Corrugated Shipping Cases

Buy your corrugated shipping cases from us to ensure perfect use on this machine!

[\(/packaging-materials/corrugated-shipping-cases/\)](/packaging-materials/corrugated-shipping-cases/)



Tech Service

Ask about our tech service and maintenance programs!

[\(/packaging-equipment-parts-tech-service/\)](/packaging-equipment-parts-tech-service/)

The Pearson CE25 case erector operates at speeds up to 25 cases per minute. All CE25 models feature an ergonomically friendly, powered, horizontal case magazine. With a vertical case presentation and compact footprint, the CE25 is ideal for limited floor space applications.

Speed

Up to 25 cases per minute

Key Differentiators

Dual opposed case erecting

Positive case selection/transfer

Features

Seals with tape or hot melt glue

Fast changeovers supported by scales, pointers, quick release handles, and HMI graphical guides

PackML compliant and UL listed control panel

Heavy-duty welded tubular frame made of mild steel, stainless steel, or low-pressure wash down

Allen-Bradley CompactLogix PLC with PanelView Color HMI

Case Size Range

Length: 8" to 24"

Width: 5.5" to 16"

Height: 3" to 18.5"

Supported Case Styles

CSSC

HSC

RSC

RSC with integral divider

Machine Size Range

Length: 12' to 13'

Width: 5'

Height: 6' to 7'

Options

LED beacons

Remote access router

Portability

Oversized and undersized cases

Auxiliary operator stations

Grace port

Controls integration

Magazine extensions

Plant-level ethernet connection

Separate glue disconnect