



# EP-08/EP-15/EP-25 Elevating Prefeeder

Designed for Floor Level Parts Loading



### Standard Features:

- All stainless steel construction
- Belting is FDA/USDA approved white 1-ply solid woven polyester fabric with 1/16" thick white PVC coating and PVC cleats
- · Hopper cleanout door
- One piece formed hopper (EP-08)
- · Panel mount controller card
- Mechanical style level sensor mounting kit proximity sensor not included (P/N LEVSENPKG1)

### Available Options:

- Elevator extensions\*
- Hopper extension for 15 and 25 ft<sup>3</sup> capacity
- Continuous welded hopper seams (EP-15/EP-25)
- · Elevator/hopper covers
- Modular plastic chain upgrade
- · Washdown motor
- NEMA 1 encased controller
- Pneumatic hopper agitator (P/N AGITATOREP08)
- Casters

\*It is strongly recommended that the frame of the prefeeder be reinforced and/ or additionally supported for elevator extensions of 36" or greater.

# Product Overview:

Hoppmann's standard EP-08/EP-15/EP-25 elevating prefeeder is designed to handle a variety of medium-sized, light weight parts. Its eight (8) cubic foot capacity hopper delivers product at an average belt speed of 32 feet per minute. The cleated elevator belt has a nominal cleat height of 2.00" and a cleat pitch of 6.00" allowing for maximum product loading. A heavy duty variable speed motor helps to ensure proper product metering.

# **Product Specifications:**

		<u>ANSI</u>	<u>Metric</u>
Α.	Overall Width	42"	1067mm
В.	Overall Length	63"	1600mm
C.	Lower Chassis Footprint	63.10"	1603mm
D.	Dump Height (Adjustable)	42"-53"	1067-1346mm
Ε.	Hopper Load Height (8 ft <sup>3</sup> )	34"	864mm
	Hopper Load Height (15 ft <sup>3</sup> )	42"	1067mm
	Hopper Load Height (25 ft <sup>3</sup> )	50"	1270mm


F. Belt Width

## Standard Models:

Part Number	EP0808XDSA	EP0808XASA
Motor Style Motor Voltage	DC 130V	AC 230/460V
Horsepower	1/4 hp	186 W
Total Equipment Weight	720 lbs.	327 kg
Hopper Capacity (EP-8)	8 ft <sup>3</sup>	227 liters
Hopper Capacity (EP-15)	15 ft <sup>3</sup>	425 liters
Hopper Capacity (EP-25)	25 ft <sup>3</sup>	708 liters

8"

203mm



Hoppmann Corporation strives to improve its products and reserves the right to change or discontinue specifications & designs shown in this brochure without notice and without incurring obligation. 06/05

#### **Packaging - Processing**

#### Bid on Equipment 1-847-683-7720

www.bid-on-equipment.com

Hoppmann Corporation Headquarters 13129 Airpark Drive • Suite 120 • Elkwood, VA 22718 Tel: 540.829.2564 • 800.368.3582 • Fax: 540.829.1724 www.hoppmann.com • email: feeder@hoppmann.com Hoppmann Corporation Manufacturing P.O. Box 879 • 291 Dillard Rd. • Madison Heights, VA 24572 Tel: 434.929.4746 • 800.543.0915 • Fax: 434.929.4959 www.hoppmann.com • email: feeder@hoppmann.com