Weighing packages up to 10 Ibs at speeds of 250 containers per minute, Alpha's CW-10 is the checkweigher for fast and accurate weighing applications. Our modular design offers the ruggedness and durability for demanding production environments. The CW-10 can achieve accuracies to 0.5 grams, depending on the application. Save money and maximize efficiencies with our seamless filler integration and feedback capabilities.

CW-10 Checkweigher



Model Specifications

Construction

Stainless steel and anodized aluminum (standard)

Direction of Travel Left to right or right to left

Conveyor Chain/Belts Nylatron, poly steel, KVP or FDA white

Weigh Indicator

3 light tower (standard) 5 light tower (optional) Others

Controls

Simplified touch screen HMI with embedded controller 100 program memory

Control Mounting

Rear-mounted control box (standard) Front-mounted, pedestal, and rotated 180° (optional)

Data Output

RS-232, ethernet, or USB

Reject Devices

Air blast, pusher, bopper, signal (only), swing gate, or special reject devices available

Reject Location

Outfeed conveyor or remote **Reject Direction**

Front, rear, or special

Electrical Requirements 110V single phase, 60 hz

Pneumatic Requirements 80 psi/4 scfm

Options: Special construction: explosion-proof, wash down, and more

Guide rails Container transfer: roller, dead plate, side belts, or timing screw Feedback: contact closure, digital, single/dual head filler, or custom

6