


# Vertical Form/Fill/Seal Machine **ULTIMA® ST**



### **Features:**

- Allen-Bradley PV 600 color touchscreen operator interface
- Off-the-shelf Allen-Bradley control system SLC 5/03 PLC
- Patented Measure, Form, Pull film advance concept
- Stepper-motor-controlled pull belts and measuring roller
- Self-centering pull belts
- Superior fiber-optic film registration system

- Exclusive, independently timed linear stager
- Durable orbital cut-off knife actuator
- More dwell time for better looking seals and increased packaging speeds
- Heavy-duty jaw assembly houses a cushion for shock and noise abatement



**Barry-Wehmiller** 













## Vertical Form/Fill/Seal Machine **ULTIMA® ST**

#### **Additional Features:**

■ RESISTANCE SEALING WITH HAYSSEN'S STEEL/HASTELLOY DIE FACES ■ QUALI-SEAL® POLYETHYLENE SEALING SYSTEM ■ EXTENDED STROKE PLATEN ASSEMBLY

## **Options:**

- ALLEN-BRADLEY PANELVIEW 1000 OPERATOR INTERFACE ■ ALLEN-BRADLEY 5/04 PLC ■ SPLICE ASSIST DEVICE ■ HOLE PUNCHES ■ TEAR NOTCHES
- CODE DATERS STAINLESS STEEL CONSTRUCTION
- Gas Flushing Static Eliminators
- PRINTERS AND OTHER SPECIALIZED OPTIONS FOR SPECIFIC INDUSTRY REQUIREMENTS ■ ACCU-TRACK® AUTOMATIC FILM TRACKING DEVICE ■ TWIN TUBE CONFIGURATIONS ■ MAPS (MAINTENANCE ALERT & Prevention System) 
  FLAT BOTTOM BAG TUCKING DEVICES ■ TOP ZIPPER ■ A WIDE VARIETY OF FEED SYSTEMS FOR DRY, LIOUID, AND DIFFICULT PRODUCTS CAN BE PROVIDED



### **Power Requirements:**

115 vac, single phase, 50/60 hz, 30 amp service

## **Air Requirements:**

2.5 scfm @ 65 psi per 10 bags per minute

### **Production Rate:**

Up to 100 bags per minute (subject to product and packaging material evaluation)

## Package Range:


Minimum 2-1/8" (54mm) Width:

> 3" (76mm) Length:

Maximum Width: 12" (305mm)

> 16" (406mm) Length:

Note: Package range specified above is for 12-16 model. Package sizes up to 15" wide by 24" long (381 mm x 610 mm) can be made on larger ULTIMA ST models.



(Dimensions shown are approximate and subject to change, consult factory for exact figures)

# **Hayssen Packaging Technologies**

A BARRY-WEHMILLER COMPANY 225 Spartangreen Boulevard www.hayssen.com sales@hayssen.com 11/03 LR

Duncan, SC 29334 USA Phone: 864/486-4000 Fax: 864/486-4412

#### Hayssen Europe Ltd.

16 Roman Way Thetford, Norfolk IP24 1XB England Phone: + 44 1842 754171 Fax: + 44 1842 751887

#### **Hayssen Latin America**

Av. José Ma. Castorena 324 - 118 Col. Cuajimalpa, 05000 México, D.F. Phone: 011-52-555-813-7770 Fax: 011-52-555-812-0987