

SPECIFICATIONS

MODEL		EZ-24 BR/SR	EZ-36 BR/SR	EZ-48 BR/SR	EZ-72 BR/SR	EZ-30-IR
Technology		Convective – (Forced Hot Air – Re-circulated)				Radiant (Infra-Red)
Standard Tunnel Opening (Note 1)		7.5" wide x 6.75" high				3" wide 6" high
Electrical Specifications	220-240VAC 50/60 Hz. Single Phase	37 Amps		74 Amps (2 x 37 Amps)		24 Amps
	220-240 VAC 50/60 Hz. Three Phase	30 Amps		60 Amps (2 x 30 Amps)		N/A
	480 VAC 50/60 Hz. Three Phase	16 Amps		32 Amps (2 x 16 Amps)		N/A
Space Requirements	Length (Note 2)	24"	36"	48"	72"	30"
	Width (Note 3)	18"				10"
	Height (Note 4)	24"				10"
Weight (lbs)		90	120	180	240	50

- Notes: 1 – Custom Tunnel opening sizes are available contact Axon Corporation.
 2 – Length of the EZ-48 and EZ-72 increase by 2" when conveyor mounted with Auto Tunnel Lift option.
 3 – Width of the tunnel can be increased to accommodate larger products.
 4 – Height of the tunnel can be increased to accommodate longer/taller sleeves.