

835 Case Packer

The standard for flexibility and reliability



The Hartness Model 835 case packer is the standard for flexibility and reliability in medium-speed intermittent motion case packing. The Model 835's robust design combined with Hartness' nearly 50 years of application engineering experience and a broad options package ensures flexible, efficient operation and a long life cycle.

Glass, plastic, cans and paperboard in both round and non-round configuration are all efficiently handled in the 835. Engineered versatility enables the machine to handle containers ranging in size from 2 ounces to 2 ½ gallons with minimal, tool-less changeover.

Containers may be packed into a variety of secondary packaging formats including RSC, tray, and display trays. Depending on size, containers may be packed into multiple tray or case configurations for increased throughput speeds. For non-round containers, an integrated high speed Laner option provides seamless laning and conveying of difficult shaped bottles. Hartness' patented "air transfer" ensures low-pressure handling and packing of difficult shaped containers including reverse tapered bottles, flasks, chimed cans and trigger bottles.

Benefits

- / Gentle and flexible handling products and formats
- / Quick and simple tool-less
- / Superior case and tray handling use of servo-controlled lugs
- / Air transfer package ensures pressure handling of lightweight to handle containers
- / Broad options package:
 - Positive placement packing containers
 - Stainless steel frame
 - Neck down packing for (
 - Integrated option for high conveying of difficult shapes
 - Automatic Central Lubrication
 - Dry Chain Lubrication
 - Bottle turner
 - Reverse feed for flexible
 - Compact change parts



835 Case Packer

General sp

ITEM DESCRIPTION


machine	Model 835
speed	Up to 30 cases per minute
container application	Round and non-round containers glass (Returnable and one-way) Pet (prb and one-way)
case application	HSC, RSC (newly erected or "reshippers") Full, 1/2 and 1/4 depth plastic crates
weight	Approximately 5,000 lbs (2269kg)
case dimensions	Length: 7-22.5 in [177.8-571.5mm] Width: 5.5-16.5 in [139.7-419.1mm] Height: 2-20 in [50.8-508mm]
voltage	240 / 460 AC or customer choice
phase	3
hz	50 / 60
amp	30 / 15-amp minimum electrical service recommended
air consumption	Ware strip-1.0 CF/cycle Air transfer-2.1 CF/cycle

The dimensions, descriptions, illustrations and other particulars in this profile are given in good faith but are not intended to and do not constitute any guarantee or warranty given by Hartness International or form any part of any contract. Photographs and/or illustrations may be shown with optional equipment or without safety guards in order to show features. Hartness International designs are covered by numerous US and International Patents.



1200 Garlington Rd / PO Box 26509
Greenville, SC 29616-1509 USA
phone: 864.297.1200 / fax: 864.297.4486
email: info@hartness.com / www.hartness.com

Model 835 with Laner



Model 835 with S-Curve Infeed

