

CUTTING EDGE TECHNOLOGY FROM THE LEADER IN MODIFIED ATMOSPHERE PACKAGING



Z-1200

The Z-1200 is the answer to high volume modified atmosphere production. Utilizing premade bags, speeds up to 9000 lbs per hour can be processed.

With a low profile and compact in design, the Z1200 can be used in plants with low ceiling heights. It also integrates with automatic feeders and scales.

A product settling shaker and bag sizer ensure uniform bag profile, optimum cube utilization and box fit.



Z-1200 Typical Uses:

Food Produce: Fresh cut produce, salads, pickles, and peppers packed in brine

Red meat: Sausage, patties, chops Poultry: Poultry up to 10 lb (5 kilo) bags Nuts and snack foods: Can replacement

Cheese: Shredded cheese

Cooked pastas and salad dressings

Industrial Electrical parts and components

The Z-1200 Design Features:

- Hygienic Design Clean-in-place system for internal cleaning. External washdown capability. Stainless steel snorkels
- Flexibility Flex-fill design efficiently handles bags from 10" x 10" to 16" x 24" Large Z handles bags up to 24" x 40", with bag weights up to 60 pounds. Easy changeover-bag lengths can be changed in minutes.
- Fast and Convenient Fills up to 30 five-pound bags per minute. PLC controller interfaces with most automatic scale systems. Self-contained, high capacity vacuum pump minimizes evacuation time. One-man operation saves labor.
- Options Product setting device gently vibrates to ease product filling, bag sizing device forms the bags to fit easily into boxes or totes. Liquid and liquid/solid fill systems are available.
- Low Profile Design

Z-1200 Specifications:

Construction

Stainless Steel/Hard Anodized Aluminum

Dimensions

Standard Z 121" x 41.5" x 48" (3073mm x 1054mm x 1219mm)

Big Z 153" x 41.5" x 68" (3886mm x 1054mm x 1727mm)

Power requirements

220/440 VAC 3 Ø; 25/15 Amp. Others on request

Air consumption

1 CFM @ 80 psi/cycle (28 liter/min @ 5.5 bar)

Seal bar lenght

Standard Z 18" - Effective Seal Length up to 18" (457mm)

Big Z 24" - Effective Seal Length up to 24" (609mm)

CE compliant