

SK 300 - 6 TECHNICAL DATA

SK / ASK	model	200	300	450	600	800	1250
PE-film max. widths as per our technical sheet		mm 200	290	440	590	790	1250
Infeed width	max.	mm 320	380	530	680	880	1350
Infeed length max. (Extension possible)		mm 250	350	350	350	350	800
Infeed height max. (Extension possible)		mm 200	290	290	290	290	350
Machine dimensions (Basic machine)							
Length		mm 1220	1670	1670	1670	1670	2500
Width		mm 760	830	980	1130	1330	1910
Height		mm 1630	1700	1700	1700	1700	1700
Infeed table height		mm	8 0 0 - 9 5 0				
Weight	(Basic machine)	kg 300	350	400	600	700	900
Power details (dependent on country of destination and machine specification)			Electrical 230 / 400 V, 50 - 60 Hz, 20 A				
			Compressed air Check power details on machine plate 500 000 - max. 800 000 PA (5 - 8 bar)				
Power consumption Basic maschine (depending on speed)			Electrical KW 0,5	0,65	0,8	1,05	1,2
Compressed air ca.			1/min. 200	240	240	300	400
Power consumption SKINETTatherm			Electrical KW 6,8	50 % reduced power consumption at constant run			
Power consumption SKINETTAshrink			Electrical KW 8,1	50 % reduced power consumption at constant run			
Power connections			Electrical	Schuko or CEEKON-plug			
			Compressed air	Connector R 1/2"			
Noise level (dependent on product)			below 70 dB(A) for soft packs				
measured according to DIN 45635, part 1 and 28							
Colour (special colour on request)			grey as per RAL 7032				